



SRIX 24016
Compartment: 1

Gage Table Information

Reporting Marks: **SRIX 24016**
Trinity File Number: T08006
Capacity: 5,950
Tare Weight: Not Available
Compartment: 1

Tank Number: 5
Table Created: 6/5/2008
Operating Stencil: Not Available

This gage table shows OUTAGE volumes (volumes of vapor space above the liquid surface). Distances shown are measured downward from the shell-full (zero outage) level to the surface of the liquid. This is from the inside top of the tank for most tank cars and from the bottom of the manway for most compartment tanks.

Inches	Gallons	Inches	Gallons	Inches	Gallons	Inches	Gallons
0.25	2	10.25	252	20.25	706	30.25	1,285
0.50	4	10.50	262	20.50	719	30.50	1,300
0.75	6	10.75	271	20.75	733	30.75	1,316
1.00	8	11.00	281	21.00	746	31.00	1,332
1.25	12	11.25	290	21.25	759	31.25	1,347
1.50	15	11.50	300	21.50	773	31.50	1,363
1.75	18	11.75	310	21.75	786	31.75	1,379
2.00	22	12.00	320	22.00	800	32.00	1,395
2.25	26	12.25	330	22.25	814	32.25	1,411
2.50	31	12.50	341	22.50	827	32.50	1,427
2.75	35	12.75	351	22.75	841	32.75	1,443
3.00	40	13.00	361	23.00	855	33.00	1,459
3.25	45	13.25	372	23.25	869	33.25	1,475
3.50	50	13.50	383	23.50	883	33.50	1,492
3.75	56	13.75	394	23.75	897	33.75	1,508
4.00	61	14.00	404	24.00	911	34.00	1,524
4.25	67	14.25	415	24.25	925	34.25	1,540
4.50	73	14.50	427	24.50	940	34.50	1,557
4.75	79	14.75	438	24.75	954	34.75	1,573
5.00	86	15.00	449	25.00	968	35.00	1,590
5.25	92	15.25	460	25.25	983	35.25	1,606
5.50	99	15.50	472	25.50	997	35.50	1,623
5.75	105	15.75	483	25.75	1,012	35.75	1,639
6.00	112	16.00	495	26.00	1,027	36.00	1,656
6.25	120	16.25	507	26.25	1,041	36.25	1,672
6.50	127	16.50	519	26.50	1,056	36.50	1,689
6.75	134	16.75	531	26.75	1,071	36.75	1,706
7.00	142	17.00	543	27.00	1,086	37.00	1,723
7.25	149	17.25	555	27.25	1,101	37.25	1,739
7.50	157	17.50	567	27.50	1,116	37.50	1,756
7.75	165	17.75	579	27.75	1,131	37.75	1,773
8.00	173	18.00	591	28.00	1,146	38.00	1,790
8.25	182	18.25	604	28.25	1,161	38.25	1,807
8.50	190	18.50	616	28.50	1,176	38.50	1,824
8.75	199	18.75	629	28.75	1,192	38.75	1,841
9.00	207	19.00	642	29.00	1,207	39.00	1,858
9.25	216	19.25	654	29.25	1,222	39.25	1,875
9.50	225	19.50	667	29.50	1,238	39.50	1,892
9.75	234	19.75	680	29.75	1,253	39.75	1,909
10.00	243	20.00	693	30.00	1,269	40.00	1,926


TRINITY RAIL.
Built to Deliver
SRIX 24016
 Compartment: 1

Gage Table Information

 Reporting Marks: **SRIX 24016**
 Trinity File Number: T08006
 Capacity: 5,950
 Tare Weight: Not Available
 Compartment: 1

 Tank Number: 5
 Table Created: 6/5/2008
 Operating Stencil: Not Available

This gage table shows OUTGAGE volumes (volumes of vapor space above the liquid surface). Distances shown are measured downward from the shell-full (zero outage) level to the surface of the liquid. This is from the inside top of the tank for most tank cars and from the bottom of the manway for most compartment tanks.

Inches	Gallons	Inches	Gallons	Inches	Gallons	Inches	Gallons
40.25	1,943	50.25	2,648	60.25	3,366	70.25	4,068
40.50	1,960	50.50	2,666	60.50	3,384	70.50	4,085
40.75	1,978	50.75	2,684	60.75	3,402	70.75	4,102
41.00	1,995	51.00	2,701	61.00	3,420	71.00	4,119
41.25	2,012	51.25	2,719	61.25	3,438	71.25	4,136
41.50	2,030	51.50	2,737	61.50	3,455	71.50	4,153
41.75	2,047	51.75	2,755	61.75	3,473	71.75	4,170
42.00	2,064	52.00	2,773	62.00	3,491	72.00	4,186
42.25	2,082	52.25	2,791	62.25	3,509	72.25	4,203
42.50	2,099	52.50	2,809	62.50	3,527	72.50	4,220
42.75	2,116	52.75	2,827	62.75	3,544	72.75	4,237
43.00	2,134	53.00	2,845	63.00	3,562	73.00	4,253
43.25	2,151	53.25	2,863	63.25	3,580	73.25	4,270
43.50	2,169	53.50	2,881	63.50	3,597	73.50	4,287
43.75	2,186	53.75	2,899	63.75	3,615	73.75	4,303
44.00	2,204	54.00	2,917	64.00	3,633	74.00	4,320
44.25	2,221	54.25	2,935	64.25	3,650	74.25	4,337
44.50	2,239	54.50	2,953	64.50	3,668	74.50	4,353
44.75	2,257	54.75	2,971	64.75	3,686	74.75	4,369
45.00	2,274	55.00	2,989	65.00	3,703	75.00	4,386
45.25	2,292	55.25	3,007	65.25	3,721	75.25	4,402
45.50	2,309	55.50	3,025	65.50	3,738	75.50	4,419
45.75	2,327	55.75	3,043	65.75	3,756	75.75	4,435
46.00	2,345	56.00	3,061	66.00	3,774	76.00	4,451
46.25	2,363	56.25	3,079	66.25	3,791	76.25	4,467
46.50	2,380	56.50	3,097	66.50	3,809	76.50	4,484
46.75	2,398	56.75	3,115	66.75	3,826	76.75	4,500
47.00	2,416	57.00	3,133	67.00	3,843	77.00	4,516
47.25	2,434	57.25	3,151	67.25	3,861	77.25	4,532
47.50	2,451	57.50	3,169	67.50	3,878	77.50	4,548
47.75	2,469	57.75	3,187	67.75	3,896	77.75	4,564
48.00	2,487	58.00	3,205	68.00	3,913	78.00	4,580
48.25	2,505	58.25	3,223	68.25	3,930	78.25	4,596
48.50	2,523	58.50	3,241	68.50	3,947	78.50	4,611
48.75	2,540	58.75	3,259	68.75	3,965	78.75	4,627
49.00	2,558	59.00	3,277	69.00	3,982	79.00	4,643
49.25	2,576	59.25	3,295	69.25	3,999	79.25	4,658
49.50	2,594	59.50	3,312	69.50	4,016	79.50	4,674
49.75	2,612	59.75	3,330	69.75	4,033	79.75	4,690
50.00	2,630	60.00	3,348	70.00	4,051	80.00	4,705

Page: 2 of 3



SRIX 24016
Compartment: 1

Gage Table Information

Reporting Marks: **SRIX 24016**
Trinity File Number: T08006
Capacity: 5,950
Tare Weight: Not Available
Compartment: 1

Tank Number: 5
Table Created: 6/5/2008
Operating Stencil: Not Available

This gage table shows OUTAGE volumes (volumes of vapor space above the liquid surface). Distances shown are measured downward from the shell-full (zero outage) level to the surface of the liquid. This is from the inside top of the tank for most tank cars and from the bottom of the manway for most compartment tanks.

Inches	Gallons	Inches	Gallons	Inches	Gallons	Inches	Gallons
80.25	4,721	90.25	5,289	100.25	5,729	110.25	5,950
80.50	4,736	90.50	5,302	100.50	5,738	110.50	5,950
80.75	4,751	90.75	5,315	100.75	5,747	110.75	5,950
81.00	4,767	91.00	5,328	101.00	5,755		
81.25	4,782	91.25	5,340	101.25	5,764		
81.50	4,797	91.50	5,353	101.50	5,772		
81.75	4,812	91.75	5,365	101.75	5,780		
82.00	4,827	92.00	5,377	102.00	5,788		
82.25	4,842	92.25	5,389	102.25	5,796		
82.50	4,857	92.50	5,402	102.50	5,804		
82.75	4,872	92.75	5,414	102.75	5,811		
83.00	4,887	93.00	5,426	103.00	5,819		
83.25	4,902	93.25	5,437	103.25	5,826		
83.50	4,917	93.50	5,449	103.50	5,833		
83.75	4,931	93.75	5,461	103.75	5,840		
84.00	4,946	94.00	5,472	104.00	5,847		
84.25	4,960	94.25	5,484	104.25	5,854		
84.50	4,975	94.50	5,495	104.50	5,860		
84.75	4,989	94.75	5,507	104.75	5,867		
85.00	5,004	95.00	5,518	105.00	5,873		
85.25	5,018	95.25	5,529	105.25	5,879		
85.50	5,032	95.50	5,540	105.50	5,885		
85.75	5,046	95.75	5,551	105.75	5,890		
86.00	5,060	96.00	5,562	106.00	5,896		
86.25	5,075	96.25	5,572	106.25	5,901		
86.50	5,088	96.50	5,583	106.50	5,906		
86.75	5,102	96.75	5,594	106.75	5,911		
87.00	5,116	97.00	5,604	107.00	5,916		
87.25	5,130	97.25	5,614	107.25	5,920		
87.50	5,144	97.50	5,625	107.50	5,924		
87.75	5,157	97.75	5,635	107.75	5,928		
88.00	5,171	98.00	5,645	108.00	5,932		
88.25	5,184	98.25	5,654	108.25	5,935		
88.50	5,198	98.50	5,664	108.50	5,939		
88.75	5,211	98.75	5,674	108.75	5,941		
89.00	5,224	99.00	5,683	109.00	5,944		
89.25	5,237	99.25	5,693	109.25	5,946		
89.50	5,251	99.50	5,702	109.50	5,947		
89.75	5,264	99.75	5,711	109.75	5,948		
90.00	5,277	100.00	5,720	110.00	5,949		



TRINITYRAIL

Built to Deliver

SRIX 24016
Compartment: 2

Gage Table Information

Reporting Marks: **SRIX 24016**
Trinity File Number: T08006
Capacity: 5,970
Tare Weight: Not Available
Compartment: 2

Tank Number: 5
Table Created: 5/27/2008
Operating Stencil: Not Available

This gage table shows OUTAGE volumes (volumes of vapor space above the liquid surface). Distances shown are measured downward from the shell-full (zero outage) level to the surface of the liquid. This is from the inside top of the tank for most tank cars and from the bottom of the manway for most compartment tanks.

Inches	Gallons	Inches	Gallons	Inches	Gallons	Inches	Gallons
0.25	1	10.25	252	20.25	708	30.25	1,288
0.50	3	10.50	262	20.50	721	30.50	1,304
0.75	5	10.75	271	20.75	735	30.75	1,320
1.00	8	11.00	281	21.00	748	31.00	1,336
1.25	11	11.25	291	21.25	761	31.25	1,351
1.50	14	11.50	301	21.50	775	31.50	1,367
1.75	18	11.75	311	21.75	788	31.75	1,383
2.00	22	12.00	321	22.00	802	32.00	1,399
2.25	26	12.25	331	22.25	816	32.25	1,415
2.50	30	12.50	341	22.50	830	32.50	1,431
2.75	35	12.75	352	22.75	843	32.75	1,447
3.00	40	13.00	362	23.00	857	33.00	1,464
3.25	45	13.25	373	23.25	871	33.25	1,480
3.50	50	13.50	383	23.50	885	33.50	1,496
3.75	55	13.75	394	23.75	900	33.75	1,512
4.00	61	14.00	405	24.00	914	34.00	1,529
4.25	67	14.25	416	24.25	928	34.25	1,545
4.50	73	14.50	427	24.50	942	34.50	1,561
4.75	79	14.75	439	24.75	957	34.75	1,578
5.00	85	15.00	450	25.00	971	35.00	1,594
5.25	92	15.25	461	25.25	986	35.25	1,611
5.50	98	15.50	473	25.50	1,000	35.50	1,628
5.75	105	15.75	484	25.75	1,015	35.75	1,644
6.00	112	16.00	496	26.00	1,030	36.00	1,661
6.25	119	16.25	508	26.25	1,044	36.25	1,678
6.50	127	16.50	520	26.50	1,059	36.50	1,694
6.75	134	16.75	532	26.75	1,074	36.75	1,711
7.00	142	17.00	544	27.00	1,089	37.00	1,728
7.25	149	17.25	556	27.25	1,104	37.25	1,745
7.50	157	17.50	568	27.50	1,119	37.50	1,762
7.75	165	17.75	580	27.75	1,134	37.75	1,778
8.00	173	18.00	593	28.00	1,149	38.00	1,795
8.25	182	18.25	605	28.25	1,165	38.25	1,812
8.50	190	18.50	618	28.50	1,180	38.50	1,829
8.75	199	18.75	631	28.75	1,195	38.75	1,846
9.00	207	19.00	643	29.00	1,211	39.00	1,863
9.25	216	19.25	656	29.25	1,226	39.25	1,881
9.50	225	19.50	669	29.50	1,241	39.50	1,898
9.75	234	19.75	682	29.75	1,257	39.75	1,915
10.00	243	20.00	695	30.00	1,273	40.00	1,932



SRIX 24016
Compartment: 2

Gage Table Information

Reporting Marks: **SRIX 24016**
Trinity File Number: T08006
Capacity: 5,970
Tare Weight: Not Available
Compartment: 2

Tank Number: 5
Table Created: 5/27/2008
Operating Stencil: Not Available

This gage table shows OUTAGE volumes (volumes of vapor space above the liquid surface). Distances shown are measured downward from the shell-full (zero outage) level to the surface of the liquid. This is from the inside top of the tank for most tank cars and from the bottom of the manway for most compartment tanks.

Inches	Gallons	Inches	Gallons	Inches	Gallons	Inches	Gallons
40.25	1,949	50.25	2,656	60.25	3,377	70.25	4,081
40.50	1,966	50.50	2,674	60.50	3,395	70.50	4,098
40.75	1,984	50.75	2,692	60.75	3,413	70.75	4,115
41.00	2,001	51.00	2,710	61.00	3,431	71.00	4,132
41.25	2,018	51.25	2,728	61.25	3,448	71.25	4,149
41.50	2,036	51.50	2,746	61.50	3,466	71.50	4,166
41.75	2,053	51.75	2,764	61.75	3,484	71.75	4,183
42.00	2,071	52.00	2,782	62.00	3,502	72.00	4,200
42.25	2,088	52.25	2,800	62.25	3,520	72.25	4,217
42.50	2,105	52.50	2,818	62.50	3,538	72.50	4,234
42.75	2,123	52.75	2,836	62.75	3,556	72.75	4,250
43.00	2,140	53.00	2,854	63.00	3,573	73.00	4,267
43.25	2,158	53.25	2,872	63.25	3,591	73.25	4,284
43.50	2,175	53.50	2,890	63.50	3,609	73.50	4,301
43.75	2,193	53.75	2,908	63.75	3,627	73.75	4,317
44.00	2,211	54.00	2,926	64.00	3,644	74.00	4,334
44.25	2,228	54.25	2,944	64.25	3,662	74.25	4,350
44.50	2,246	54.50	2,962	64.50	3,680	74.50	4,367
44.75	2,264	54.75	2,980	64.75	3,697	74.75	4,384
45.00	2,281	55.00	2,999	65.00	3,715	75.00	4,400
45.25	2,299	55.25	3,017	65.25	3,733	75.25	4,416
45.50	2,317	55.50	3,035	65.50	3,750	75.50	4,433
45.75	2,334	55.75	3,053	65.75	3,768	75.75	4,449
46.00	2,352	56.00	3,071	66.00	3,786	76.00	4,466
46.25	2,370	56.25	3,089	66.25	3,803	76.25	4,482
46.50	2,388	56.50	3,107	66.50	3,821	76.50	4,498
46.75	2,405	56.75	3,125	66.75	3,838	76.75	4,514
47.00	2,423	57.00	3,143	67.00	3,856	77.00	4,530
47.25	2,441	57.25	3,161	67.25	3,873	77.25	4,546
47.50	2,459	57.50	3,179	67.50	3,891	77.50	4,562
47.75	2,477	57.75	3,197	67.75	3,908	77.75	4,578
48.00	2,495	58.00	3,215	68.00	3,925	78.00	4,594
48.25	2,513	58.25	3,233	68.25	3,943	78.25	4,610
48.50	2,530	58.50	3,251	68.50	3,960	78.50	4,626
48.75	2,548	58.75	3,269	68.75	3,977	78.75	4,642
49.00	2,566	59.00	3,287	69.00	3,995	79.00	4,658
49.25	2,584	59.25	3,305	69.25	4,012	79.25	4,673
49.50	2,602	59.50	3,323	69.50	4,029	79.50	4,689
49.75	2,620	59.75	3,341	69.75	4,046	79.75	4,705
50.00	2,638	60.00	3,359	70.00	4,064	80.00	4,720

Page: 2 of 3



Build to Deliver

SRIX 24016
Compartment: 2

Gage Table Information

Reporting Marks: **SRIX 24016**
Trinity File Number: T08006
Capacity: 5,970
Tare Weight: Not Available
Compartment: 2

Tank Number: 5
Table Created: 5/27/2008
Operating Stencil: Not Available

This gage table shows OUTAGE volumes (volumes of vapor space above the liquid surface). Distances shown are measured downward from the shell-full (zero outage) level to the surface of the liquid. This is from the inside top of the tank for most tank cars and from the bottom of the manway for most compartment tanks.

Inches	Gallons	Inches	Gallons	Inches	Gallons	Inches	Gallons
80.25	4,736	90.25	5,307	100.25	5,748	110.25	5,970
80.50	4,751	90.50	5,320	100.50	5,757	110.50	5,970
80.75	4,767	90.75	5,332	100.75	5,766	110.75	5,970
81.00	4,782	91.00	5,345	101.00	5,774		
81.25	4,797	91.25	5,358	101.25	5,783		
81.50	4,813	91.50	5,370	101.50	5,791		
81.75	4,828	91.75	5,383	101.75	5,799		
82.00	4,843	92.00	5,395	102.00	5,807		
82.25	4,858	92.25	5,407	102.25	5,815		
82.50	4,873	92.50	5,419	102.50	5,823		
82.75	4,888	92.75	5,431	102.75	5,831		
83.00	4,903	93.00	5,443	103.00	5,838		
83.25	4,918	93.25	5,455	103.25	5,845		
83.50	4,933	93.50	5,467	103.50	5,853		
83.75	4,947	93.75	5,479	103.75	5,860		
84.00	4,962	94.00	5,490	104.00	5,867		
84.25	4,977	94.25	5,502	104.25	5,873		
84.50	4,991	94.50	5,513	104.50	5,880		
84.75	5,006	94.75	5,525	104.75	5,886		
85.00	5,020	95.00	5,536	105.00	5,892		
85.25	5,034	95.25	5,547	105.25	5,898		
85.50	5,049	95.50	5,558	105.50	5,904		
85.75	5,063	95.75	5,569	105.75	5,910		
86.00	5,077	96.00	5,580	106.00	5,916		
86.25	5,091	96.25	5,591	106.25	5,921		
86.50	5,105	96.50	5,601	106.50	5,926		
86.75	5,119	96.75	5,612	106.75	5,931		
87.00	5,133	97.00	5,622	107.00	5,935		
87.25	5,147	97.25	5,633	107.25	5,940		
87.50	5,160	97.50	5,643	107.50	5,944		
87.75	5,174	97.75	5,653	107.75	5,948		
88.00	5,188	98.00	5,663	108.00	5,952		
88.25	5,201	98.25	5,673	108.25	5,955		
88.50	5,215	98.50	5,683	108.50	5,958		
88.75	5,228	98.75	5,693	108.75	5,961		
89.00	5,241	99.00	5,702	109.00	5,964		
89.25	5,255	99.25	5,712	109.25	5,966		
89.50	5,268	99.50	5,721	109.50	5,967		
89.75	5,281	99.75	5,730	109.75	5,968		
90.00	5,294	100.00	5,739	110.00	5,969		

Page: 3 of 3



SRIX 24016
Compartment: 3

Gage Table Information

Reporting Marks: **SRIX 24016**
Trinity File Number: T08006
Capacity: 5,950
Tare Weight: Not Available
Compartment: 3

Tank Number: 5
Table Created: 5/28/2008
Operating Stencil: Not Available

This gage table shows OUTAGE volumes (volumes of vapor space above the liquid surface). Distances shown are measured downward from the shell-full (zero outage) level to the surface of the liquid. This is from the inside top of the tank for most tank cars and from the bottom of the manway for most compartment tanks.

Inches	Gallons	Inches	Gallons	Inches	Gallons	Inches	Gallons
0.25	1	10.25	252	20.25	706	30.25	1,284
0.50	3	10.50	261	20.50	719	30.50	1,300
0.75	6	10.75	271	20.75	733	30.75	1,316
1.00	8	11.00	280	21.00	746	31.00	1,332
1.25	11	11.25	290	21.25	759	31.25	1,347
1.50	15	11.50	300	21.50	773	31.50	1,363
1.75	18	11.75	310	21.75	786	31.75	1,379
2.00	22	12.00	320	22.00	800	32.00	1,395
2.25	26	12.25	330	22.25	813	32.25	1,411
2.50	30	12.50	340	22.50	827	32.50	1,427
2.75	35	12.75	351	22.75	841	32.75	1,443
3.00	40	13.00	361	23.00	855	33.00	1,459
3.25	45	13.25	372	23.25	869	33.25	1,475
3.50	50	13.50	383	23.50	883	33.50	1,492
3.75	55	13.75	393	23.75	897	33.75	1,508
4.00	61	14.00	404	24.00	911	34.00	1,524
4.25	67	14.25	415	24.25	925	34.25	1,540
4.50	73	14.50	426	24.50	940	34.50	1,557
4.75	79	14.75	437	24.75	954	34.75	1,573
5.00	85	15.00	449	25.00	968	35.00	1,590
5.25	92	15.25	460	25.25	983	35.25	1,606
5.50	98	15.50	472	25.50	997	35.50	1,623
5.75	105	15.75	483	25.75	1,012	35.75	1,639
6.00	112	16.00	495	26.00	1,027	36.00	1,656
6.25	119	16.25	507	26.25	1,041	36.25	1,673
6.50	127	16.50	518	26.50	1,056	36.50	1,689
6.75	134	16.75	530	26.75	1,071	36.75	1,706
7.00	141	17.00	542	27.00	1,086	37.00	1,723
7.25	149	17.25	554	27.25	1,101	37.25	1,739
7.50	157	17.50	567	27.50	1,116	37.50	1,756
7.75	165	17.75	579	27.75	1,131	37.75	1,773
8.00	173	18.00	591	28.00	1,146	38.00	1,790
8.25	181	18.25	604	28.25	1,161	38.25	1,807
8.50	190	18.50	616	28.50	1,176	38.50	1,824
8.75	198	18.75	629	28.75	1,192	38.75	1,841
9.00	207	19.00	642	29.00	1,207	39.00	1,858
9.25	216	19.25	654	29.25	1,222	39.25	1,875
9.50	225	19.50	667	29.50	1,238	39.50	1,892
9.75	234	19.75	680	29.75	1,253	39.75	1,909
10.00	243	20.00	693	30.00	1,269	40.00	1,926

Page: 1 of 3


TRINITY RAIL
Build to Deliver
SRIX 24016
 Compartment: 3

Gage Table Information

 Reporting Marks: **SRIX 24016**
 Trinity File Number: T08006
 Capacity: 5,950
 Tare Weight: Not Available
 Compartment: 3

 Tank Number: 5
 Table Created: 5/28/2008
 Operating Stencil: Not Available

This gage table shows OUTGAGE volumes (volumes of vapor space above the liquid surface). Distances shown are measured downward from the shell-full (zero outage) level to the surface of the liquid. This is from the inside top of the tank for most tank cars and from the bottom of the manway for most compartment tanks.

Inches	Gallons	Inches	Gallons	Inches	Gallons	Inches	Gallons
40.25	1,943	50.25	2,648	60.25	3,366	70.25	4,068
40.50	1,961	50.50	2,666	60.50	3,384	70.50	4,085
40.75	1,978	50.75	2,684	60.75	3,402	70.75	4,102
41.00	1,995	51.00	2,702	61.00	3,420	71.00	4,119
41.25	2,012	51.25	2,720	61.25	3,438	71.25	4,136
41.50	2,030	51.50	2,738	61.50	3,456	71.50	4,153
41.75	2,047	51.75	2,756	61.75	3,474	71.75	4,170
42.00	2,064	52.00	2,774	62.00	3,491	72.00	4,187
42.25	2,082	52.25	2,792	62.25	3,509	72.25	4,204
42.50	2,099	52.50	2,809	62.50	3,527	72.50	4,220
42.75	2,117	52.75	2,827	62.75	3,545	72.75	4,237
43.00	2,134	53.00	2,845	63.00	3,562	73.00	4,254
43.25	2,151	53.25	2,863	63.25	3,580	73.25	4,271
43.50	2,169	53.50	2,881	63.50	3,598	73.50	4,287
43.75	2,186	53.75	2,899	63.75	3,616	73.75	4,304
44.00	2,204	54.00	2,917	64.00	3,633	74.00	4,320
44.25	2,222	54.25	2,935	64.25	3,651	74.25	4,337
44.50	2,239	54.50	2,953	64.50	3,669	74.50	4,353
44.75	2,257	54.75	2,971	64.75	3,686	74.75	4,370
45.00	2,274	55.00	2,989	65.00	3,704	75.00	4,386
45.25	2,292	55.25	3,007	65.25	3,721	75.25	4,403
45.50	2,310	55.50	3,025	65.50	3,739	75.50	4,419
45.75	2,327	55.75	3,043	65.75	3,756	75.75	4,435
46.00	2,345	56.00	3,061	66.00	3,774	76.00	4,452
46.25	2,363	56.25	3,079	66.25	3,791	76.25	4,468
46.50	2,380	56.50	3,097	66.50	3,809	76.50	4,484
46.75	2,398	56.75	3,115	66.75	3,826	76.75	4,500
47.00	2,416	57.00	3,133	67.00	3,844	77.00	4,516
47.25	2,434	57.25	3,151	67.25	3,861	77.25	4,532
47.50	2,451	57.50	3,169	67.50	3,879	77.50	4,548
47.75	2,469	57.75	3,187	67.75	3,896	77.75	4,564
48.00	2,487	58.00	3,205	68.00	3,913	78.00	4,580
48.25	2,505	58.25	3,223	68.25	3,931	78.25	4,596
48.50	2,523	58.50	3,241	68.50	3,948	78.50	4,612
48.75	2,541	58.75	3,259	68.75	3,965	78.75	4,628
49.00	2,558	59.00	3,277	69.00	3,982	79.00	4,643
49.25	2,576	59.25	3,295	69.25	4,000	79.25	4,659
49.50	2,594	59.50	3,313	69.50	4,017	79.50	4,675
49.75	2,612	59.75	3,331	69.75	4,034	79.75	4,690
50.00	2,630	60.00	3,349	70.00	4,051	80.00	4,706

Page: 2 of 3


TRINITY RAIL,
Built to Deliver
SRIX 24016
 Compartment: 3

Gage Table Information

 Reporting Marks: **SRIX 24016**
 Trinity File Number: T08006
 Capacity: 5,950
 Tare Weight: Not Available
 Compartment: 3

 Tank Number: 5
 Table Created: 5/28/2008
 Operating Stencil: Not Available

This gage table shows OUTGAGE volumes (volumes of vapor space above the liquid surface). Distances shown are measured downward from the shell-full (zero outage) level to the surface of the liquid. This is from the inside top of the tank for most tank cars and from the bottom of the manway for most compartment tanks.

Inches	Gallons	Inches	Gallons	Inches	Gallons	Inches	Gallons
80.25	4,721	90.25	5,290	100.25	5,730	110.25	5,950
80.50	4,736	90.50	5,303	100.50	5,738	110.50	5,950
80.75	4,752	90.75	5,315	100.75	5,747	110.75	5,950
81.00	4,767	91.00	5,328	101.00	5,756		
81.25	4,782	91.25	5,341	101.25	5,764		
81.50	4,798	91.50	5,353	101.50	5,772		
81.75	4,813	91.75	5,365	101.75	5,780		
82.00	4,828	92.00	5,378	102.00	5,788		
82.25	4,843	92.25	5,390	102.25	5,796		
82.50	4,858	92.50	5,402	102.50	5,804		
82.75	4,873	92.75	5,414	102.75	5,812		
83.00	4,888	93.00	5,426	103.00	5,819		
83.25	4,902	93.25	5,438	103.25	5,826		
83.50	4,917	93.50	5,450	103.50	5,834		
83.75	4,932	93.75	5,461	103.75	5,841		
84.00	4,946	94.00	5,473	104.00	5,847		
84.25	4,961	94.25	5,484	104.25	5,854		
84.50	4,975	94.50	5,496	104.50	5,861		
84.75	4,990	94.75	5,507	104.75	5,867		
85.00	5,004	95.00	5,518	105.00	5,873		
85.25	5,018	95.25	5,529	105.25	5,879		
85.50	5,033	95.50	5,540	105.50	5,885		
85.75	5,047	95.75	5,551	105.75	5,891		
86.00	5,061	96.00	5,562	106.00	5,896		
86.25	5,075	96.25	5,573	106.25	5,901		
86.50	5,089	96.50	5,584	106.50	5,906		
86.75	5,103	96.75	5,594	106.75	5,911		
87.00	5,117	97.00	5,604	107.00	5,916		
87.25	5,130	97.25	5,615	107.25	5,920		
87.50	5,144	97.50	5,625	107.50	5,925		
87.75	5,158	97.75	5,635	107.75	5,928		
88.00	5,171	98.00	5,645	108.00	5,932		
88.25	5,185	98.25	5,655	108.25	5,936		
88.50	5,198	98.50	5,665	108.50	5,939		
88.75	5,212	98.75	5,674	108.75	5,941		
89.00	5,225	99.00	5,684	109.00	5,944		
89.25	5,238	99.25	5,693	109.25	5,946		
89.50	5,251	99.50	5,702	109.50	5,947		
89.75	5,264	99.75	5,712	109.75	5,948		
90.00	5,277	100.00	5,721	110.00	5,949		

Page: 3 of 3


TRINITY RAIL
Brill to Deliver
SRIX 24016
 Compartment: 4

Gage Table Information

 Reporting Marks: **SRIX 24016**
 Trinity File Number: T08006
 Capacity: 5,980
 Tare Weight: Not Available
 Compartment: 4

 Tank Number: 5
 Table Created: 6/5/2008
 Operating Stencil: Not Available

This gage table shows OUTAGE volumes (volumes of vapor space above the liquid surface). Distances shown are measured downward from the shell-full (zero outage) level to the surface of the liquid. This is from the inside top of the tank for most tank cars and from the bottom of the manway for most compartment tanks.

Inches	Gallons	Inches	Gallons	Inches	Gallons	Inches	Gallons
0.25	2	10.25	254	20.25	710	30.25	1,291
0.50	4	10.50	263	20.50	723	30.50	1,307
0.75	6	10.75	272	20.75	736	30.75	1,323
1.00	9	11.00	282	21.00	750	31.00	1,338
1.25	12	11.25	292	21.25	763	31.25	1,354
1.50	15	11.50	302	21.50	777	31.50	1,370
1.75	19	11.75	312	21.75	790	31.75	1,386
2.00	22	12.00	322	22.00	804	32.00	1,402
2.25	27	12.25	332	22.25	818	32.25	1,418
2.50	31	12.50	342	22.50	832	32.50	1,434
2.75	36	12.75	353	22.75	846	32.75	1,451
3.00	40	13.00	363	23.00	859	33.00	1,467
3.25	45	13.25	374	23.25	873	33.25	1,483
3.50	51	13.50	385	23.50	888	33.50	1,499
3.75	56	13.75	396	23.75	902	33.75	1,516
4.00	62	14.00	407	24.00	916	34.00	1,532
4.25	68	14.25	418	24.25	930	34.25	1,548
4.50	74	14.50	429	24.50	945	34.50	1,565
4.75	80	14.75	440	24.75	959	34.75	1,581
5.00	86	15.00	451	25.00	973	35.00	1,598
5.25	93	15.25	463	25.25	988	35.25	1,614
5.50	99	15.50	474	25.50	1,003	35.50	1,631
5.75	106	15.75	486	25.75	1,017	35.75	1,648
6.00	113	16.00	498	26.00	1,032	36.00	1,664
6.25	120	16.25	509	26.25	1,047	36.25	1,681
6.50	127	16.50	521	26.50	1,062	36.50	1,698
6.75	135	16.75	533	26.75	1,077	36.75	1,715
7.00	142	17.00	545	27.00	1,092	37.00	1,731
7.25	150	17.25	558	27.25	1,107	37.25	1,748
7.50	158	17.50	570	27.50	1,122	37.50	1,765
7.75	166	17.75	582	27.75	1,137	37.75	1,782
8.00	174	18.00	595	28.00	1,152	38.00	1,799
8.25	183	18.25	607	28.25	1,167	38.25	1,816
8.50	191	18.50	620	28.50	1,183	38.50	1,833
8.75	200	18.75	632	28.75	1,198	38.75	1,850
9.00	208	19.00	645	29.00	1,213	39.00	1,867
9.25	217	19.25	658	29.25	1,229	39.25	1,884
9.50	226	19.50	671	29.50	1,244	39.50	1,902
9.75	235	19.75	684	29.75	1,260	39.75	1,919
10.00	244	20.00	697	30.00	1,275	40.00	1,936

Page: 1 of 3


TRINITY RAIL
Built to Deliver
SRIX 24016
 Compartment: 4

Gage Table Information

 Reporting Marks: **SRIX 24016**
 Trinity File Number: T08006
 Capacity: 5,980
 Tare Weight: Not Available
 Compartment: 4

 Tank Number: 5
 Table Created: 6/5/2008
 Operating Stencil: Not Available

This gage table shows OUTGAGE volumes (volumes of vapor space above the liquid surface). Distances shown are measured downward from the shell-full (zero outage) level to the surface of the liquid. This is from the inside top of the tank for most tank cars and from the bottom of the manway for most compartment tanks.

Inches	Gallons	Inches	Gallons	Inches	Gallons	Inches	Gallons
40.25	1,953	50.25	2,661	60.25	3,383	70.25	4,088
40.50	1,971	50.50	2,679	60.50	3,401	70.50	4,105
40.75	1,988	50.75	2,697	60.75	3,419	70.75	4,122
41.00	2,005	51.00	2,715	61.00	3,437	71.00	4,139
41.25	2,022	51.25	2,733	61.25	3,455	71.25	4,156
41.50	2,040	51.50	2,751	61.50	3,473	71.50	4,173
41.75	2,057	51.75	2,769	61.75	3,491	71.75	4,190
42.00	2,075	52.00	2,787	62.00	3,509	72.00	4,207
42.25	2,092	52.25	2,805	62.25	3,526	72.25	4,224
42.50	2,110	52.50	2,823	62.50	3,544	72.50	4,241
42.75	2,127	52.75	2,841	62.75	3,562	72.75	4,258
43.00	2,145	53.00	2,860	63.00	3,580	73.00	4,275
43.25	2,162	53.25	2,878	63.25	3,598	73.25	4,292
43.50	2,180	53.50	2,896	63.50	3,616	73.50	4,308
43.75	2,197	53.75	2,914	63.75	3,633	73.75	4,325
44.00	2,215	54.00	2,932	64.00	3,651	74.00	4,342
44.25	2,233	54.25	2,950	64.25	3,669	74.25	4,358
44.50	2,250	54.50	2,968	64.50	3,687	74.50	4,375
44.75	2,268	54.75	2,986	64.75	3,704	74.75	4,391
45.00	2,286	55.00	3,004	65.00	3,722	75.00	4,408
45.25	2,303	55.25	3,022	65.25	3,740	75.25	4,424
45.50	2,321	55.50	3,040	65.50	3,757	75.50	4,441
45.75	2,339	55.75	3,058	65.75	3,775	75.75	4,457
46.00	2,357	56.00	3,076	66.00	3,793	76.00	4,474
46.25	2,375	56.25	3,095	66.25	3,810	76.25	4,490
46.50	2,392	56.50	3,113	66.50	3,828	76.50	4,506
46.75	2,410	56.75	3,131	66.75	3,845	76.75	4,522
47.00	2,428	57.00	3,149	67.00	3,863	77.00	4,538
47.25	2,446	57.25	3,167	67.25	3,880	77.25	4,555
47.50	2,464	57.50	3,185	67.50	3,898	77.50	4,571
47.75	2,482	57.75	3,203	67.75	3,915	77.75	4,587
48.00	2,500	58.00	3,221	68.00	3,933	78.00	4,603
48.25	2,517	58.25	3,239	68.25	3,950	78.25	4,619
48.50	2,535	58.50	3,257	68.50	3,967	78.50	4,634
48.75	2,553	58.75	3,275	68.75	3,985	78.75	4,650
49.00	2,571	59.00	3,293	69.00	4,002	79.00	4,666
49.25	2,589	59.25	3,311	69.25	4,019	79.25	4,682
49.50	2,607	59.50	3,329	69.50	4,036	79.50	4,697
49.75	2,625	59.75	3,347	69.75	4,054	79.75	4,713
50.00	2,643	60.00	3,365	70.00	4,071	80.00	4,729

Page: 2 of 3



TRINITYRAIL

Built to Deliver

SRIX 24016
Compartment: 4

Gage Table Information

Reporting Marks: **SRIX 24016**
Trinity File Number: T08006
Capacity: 5,980
Tare Weight: Not Available
Compartment: 4

Tank Number: 5
Table Created: 6/5/2008
Operating Stencil: Not Available

This gage table shows OUTAGE volumes (volumes of vapor space above the liquid surface). Distances shown are measured downward from the shell-full (zero outage) level to the surface of the liquid. This is from the inside top of the tank for most tank cars and from the bottom of the manway for most compartment tanks.

Inches	Gallons	Inches	Gallons	Inches	Gallons	Inches	Gallons
80.25	4,744	90.25	5,316	100.25	5,758	110.25	5,980
80.50	4,760	90.50	5,329	100.50	5,767	110.50	5,980
80.75	4,775	90.75	5,342	100.75	5,776	110.75	5,980
81.00	4,791	91.00	5,354	101.00	5,784		
81.25	4,806	91.25	5,367	101.25	5,793		
81.50	4,821	91.50	5,379	101.50	5,801		
81.75	4,836	91.75	5,392	101.75	5,809		
82.00	4,852	92.00	5,404	102.00	5,817		
82.25	4,867	92.25	5,417	102.25	5,825		
82.50	4,882	92.50	5,429	102.50	5,833		
82.75	4,897	92.75	5,441	102.75	5,841		
83.00	4,912	93.00	5,453	103.00	5,848		
83.25	4,926	93.25	5,465	103.25	5,856		
83.50	4,941	93.50	5,477	103.50	5,863		
83.75	4,956	93.75	5,488	103.75	5,870		
84.00	4,971	94.00	5,500	104.00	5,877		
84.25	4,985	94.25	5,512	104.25	5,883		
84.50	5,000	94.50	5,523	104.50	5,890		
84.75	5,014	94.75	5,534	104.75	5,896		
85.00	5,029	95.00	5,546	105.00	5,903		
85.25	5,043	95.25	5,557	105.25	5,909		
85.50	5,057	95.50	5,568	105.50	5,914		
85.75	5,072	95.75	5,579	105.75	5,920		
86.00	5,086	96.00	5,590	106.00	5,926		
86.25	5,100	96.25	5,601	106.25	5,931		
86.50	5,114	96.50	5,611	106.50	5,936		
86.75	5,128	96.75	5,622	106.75	5,941		
87.00	5,142	97.00	5,632	107.00	5,946		
87.25	5,156	97.25	5,643	107.25	5,950		
87.50	5,169	97.50	5,653	107.50	5,954		
87.75	5,183	97.75	5,663	107.75	5,958		
88.00	5,197	98.00	5,673	108.00	5,962		
88.25	5,210	98.25	5,683	108.25	5,965		
88.50	5,224	98.50	5,693	108.50	5,969		
88.75	5,237	98.75	5,702	108.75	5,971		
89.00	5,251	99.00	5,712	109.00	5,974		
89.25	5,264	99.25	5,721	109.25	5,976		
89.50	5,277	99.50	5,731	109.50	5,977		
89.75	5,290	99.75	5,740	109.75	5,978		
90.00	5,303	100.00	5,749	110.00	5,979		