



CAM2 ATF D/M
Product Code #309

CAM2 ATF D/M Automatic Transmission Fluid

CAM2 ATF D/M is a multipurpose automatic transmission fluid especially designed to meet the service requirements of a wide variety of applications. CAM2 ATF D/M is designed for newer generation, electronically controlled transmissions. It is suitable for use in transmissions built by General Motors, Daimler Chrysler, Ford (except where Type F required), and most foreign manufacturers, where a DEXRON® III H, DEXRON® III G, DEXRON® IIE, MERCON®, or Type A Suffix A performance level transmission fluid is specified. CAM2 ATF D/M meets the performance requirements of Allison Transmission Division C-4, and major hydraulic manufacturers' requirements for anti-wear hydraulic fluids.

CAM2 ATF D/M recommended for applications requiring:

- DEXRON® III H, DEXRON® III G, DEXRON® IIE, MERCON®, or Type A Suffix A
- MERCON®, M2C138-CJ or M2C 166-H Fluids
- When Allison C-4 Fluids and Caterpillar TO-2 Fluids

CAM2 ATF D/M can also be used:

- in Chrysler transmissions except where Chrysler MS-9602 or MS-7 176 is required (top-off is acceptable)
- in all 1979 or newer transmissions built by Ford (exceptions: Ford FMX and pre-1980 C-4 transmissions and where Mercon V is required)
- in some hydraulic and compressor systems where low temperature flowability is required
- in many powershift transmissions, torque converters and hydrostatic transmissions

*CAM2 ATF D/M Automatic Transmission Fluid cannot be used in GM transmissions requiring the use of DEXRON® VI automatic transmission fluid. CAM2 ATF DEXRON® VI should be used in these applications. Always consult your owner's manual for recommendations.

Contact your CAM2 representative or CAM2 distributor for additional information.

**PRODUCT
BULLETIN**

www.CAM2.COM
800-338-CAM2

CAM2 ATF D/M

Automatic Transmission Fluid

BENEFITS:

- Superior cold temperature performance characteristics
- Wide range of seal compatibility
- Excellent wear protection and oxidation resistance
- Fortified against rust and corrosion
- Meets requirements for foam protection
- Superior frictional characteristics with excellent friction retention and smooth shifting

TYPICAL PROPERTIES

ATF GRADE:	D/M
Gravity, API, ASTM D 287	32
Pounds per Gallon	7.2
Flash Point, COC, °F (°C) ASTM D 92	365 (185)
Fire Point, COC, °F (°C) ASTM D 92	428 (220)
Viscosity cSt, ASTM D 445, at 40°C	32.8
Viscosity cSt, at 100 °C	7.2
Viscosity cP, at -40°C, ASTM D2983	17,500
Viscosity cP, at -20°C	1,150
Viscosity Index, ASTM D 2270	192
Pour Point, °F (°C) ASTM D 97	-54 (-48)
Color	Red

Contact your CAM2 representative or CAM2 distributor for additional information.

**PRODUCT
BULLETIN**

www.CAM2.COM
800-338-CAM2

Revised 5/15/2010