

CAM2[®]
INTERNATIONAL, LLC

CAM2 Synavex™
Full Synthetic



CAM2 Synavex™ 0W-20
100% Full Synthetic Motor Oil
API SN-RC and ILSAC GF-5
Product Code # 383

CAM2 SYNAVEX™ 0W-20, 5W-20, 5W-30 and 10W-30 are advanced formula **100% FULL SYNTHETIC** fully licensed API SN-RC and ILSAC GF-5 multi-grade engine oils designed for vehicles operating under severe driving or extreme temperature conditions. Compared to conventional motor oils, they provided improved engine cleanliness and high temperature deposit protection. These products also help reduce oil consumption and provide exceptional cold flow properties.

Exceeds ILSAC GF-5 Standards and API Service SN-RC

- Advanced Wear, Varnish & Sludge Protection
- Superior Protection Against Thermal Breakdown
- Outstanding Resource Conserving Performance

CAM2 SYNAVEX™ 0W-20 is a premium quality, full synthetic engine oil formulated from selected superior base oils and advanced high performance engine oil additive technology.

CAM2 SYNAVEX™ 0W-20 full synthetic engine oil is formulated with low friction additives to help improve fuel economy where SAE 0W-20 is recommended and to provide outstanding engine protection. CAM2 SYNAVEX™ meets or exceeds the latest American Petroleum Institute (API) SN-RC and car manufacturers ILSAC GF-5 service classification. CAM2 SYNAVEX™ engine oils are designed especially for turbo-charged and high RPM engines which experience high heat and they provide quick flow to critical parts at start up to reduce wear. CAM2 SYNAVEX™ is the engine oil of choice for passenger cars, light trucks, powerboats, motorcycles and other stationary and mobile equipment when engine life and performance is important. CAM2 SYNAVEX™ also meets all previous service classifications: API SM, SL, SJ, SH, SG, SF and ILSAC GF-4, GF-3, etc.

CAM2 SYNAVEX™ 0W-20, 5W-20, 5W-30, & 10W-30 are designed especially for turbo-charged and high RPM engines which experience high heat. They provide quick flow to critical parts at start up to reduce wear. CAM2 SYNAVEX™ MOTOR OILS can be used in virtually all services for all gasoline engines, domestic and foreign. CAM2 SYNAVEX™ MOTOR OILS are fully compatible with all other synthetic and petroleum based engine oils.

- Excellent protection from deposits at all operating temperatures
- Excellent anti-wear, anti-foaming, anti-rust and corrosion protection
- Excellent cold cranking capabilities
- Excellent protection against accelerated oil consumption

Contact your CAM2 representative or CAM2 distributor for additional information.

**PRODUCT
BULLETIN**

www.CAM2.COM
800-338-CAM2

APPLICATIONS

CAM2 SYNAVEX™ 0W-20, 5W-20, 5W-30 and 10W-30 may be recommended for the following uses:

- When SN-RC, SM, SL, SJ, SH, SG, SF, SE, SD or SC oils are required
- When ILSAC GF-5, GF-4, GF-3, GF-2 oils are required
- When former MIL-L-46152D oils performance level is required
- When GM 6094M
- When Ford M2C153H, M2C930-A(5W-20), M2C929-A(5W-30)
- When DaimlerChrysler MS10797 (5W-20), 10796 (5W-30), 10798 (10W-30), MS6395M
- In gasoline engines and turbo-charged engines

TYPICAL PROPERTIES

SAE GRADE		0W20	5W20	5W30	10W30
Product Code		383	395	393	394
Density	lb/gal	7.1	7.2	7.12	7.11
API Gravity		35.52	34.95	34.85	34.05
Cold Crank Simulation	mPa/s		5346	3907	2388
Viscosity @ 40C	cSt	44.5	47.57	60.48	63.72
Viscosity @ 100C	cSt	8.46	8.55	10.42	10.29
Viscosity Index		170	159	162	149
NOACK			13.8	10.8	11
Color ASTM		2.5	3	3	3
Water and Sediment	(Pass / Fail)	PASS	PASS	PASS	PASS
Appearance		CLEAR	CLEAR	CLEAR	CLEAR
Pour Point: °C		-48	-45	-45	-42
Flash Point: °C		216	225	240	250
Ca		2100	2100	2100	2100
P		700	700	700	700
Zn		850	850	850	850

Contact your CAM2 representative or CAM2 distributor for additional information.

**PRODUCT
BULLETIN**

www.CAM2.COM
800-338-CAM2

Revised 10/26/2010