

CAM2[®]
INTERNATIONAL, LLC

Super HD Premium Plus (07) 10W-30

CAM2 Super HD Premium Plus (07) 10W-30

Product Code # 344



CAM2 Super HD Premium Plus (07) 10W-30, through the use of premium quality Group II base stocks and up-to-date additive technology, is formulated to provide the highest levels of equipment protection available. CAM2 Super HD Premium Plus (07) 10W-30 with next generation soot control meets the latest API CJ-4, Cummins CES 20081, Volvo VDS-4, Mack EO-O Premium Plus (07), Caterpillar ECF-3, and Detroit Diesel Power Guard 93K218.

CAM2 Super HD Premium Plus (07) 10W-30 is a premium quality, heavy-duty multi-grade oils for all- season use in diesel powered or a mix of gasoline and diesel powered equipment. It meets or exceeds the warranty and service requirements of virtually all diesel and gasoline engine manufactures. It can be recommended to both newer and older engines. Especially designed for today's high-performance, low-emissions diesel engine equipped with Exhaust Gas Recirculation (EGR) and Diesel Particulate Filter.

Contact your CAM2 representative or CAM2 distributor for additional information.

**PRODUCT
BULLETIN**

www.CAM2.COM
800-338-CAM2

CAM2 Super HD Premium Plus (07) 10W-30

APPLICATIONS

CAM2 Super HD Premium Plus (07) 10W-30 may be recommended for the following uses:

- When CJ-4, CI-4 PLUS, CI-4, CH-4, CG-4, CF-4, CF, CF-2, oils are required
- When SM, SL, SJ, SH, SG, SF, SE, SD, SC oils are required
- When a US Military CID A-A-52306 performance level is required
- When MIL-L-210E/F oils performance level is required
- ACEA E5-02, JASO DHD-1, GLOBAL DHD-1
- When GM 4718M/6094M and Ford M2C153-E oils are required
- In all diesel and gasoline engines, including turbo-charged models
- In Detroit Diesel engines Power Guard Oil is required
- In Caterpillar engines ECF-3
- In Mack engines (EO-O PREMIUM PLUS (07)**, EO-N PREMIUM PLUS**, EO-M Plus, EO-M, EO-L Plus, EO-L, EO-K/2
- In Cummins engines CES 20071, 20076, 20077, 20078, 20081
- In Volvo VDS-4**, VDS-3, VDS-2 and VDS engines
- In Caterpillar drive trains (TO-2 approved)
- When Allison C-3/C-4 fluids are required
- Mercedes Benz MB 228.5**

** OEM Specification Developed Around SAE 15W-40 Viscosity

Product Code 344

Property

Gravity, API

Typical

30.6

Viscosity:

cSt @ 40c

70

cST @ 100c

11.1

Viscosity Index

148

Pour Point: c

-40

Flash Point: c

226

Borderline Pumping: c

-25

Sulfated Ash wt%

1

Total Base Number

8

API Service

**CJ-4, CI-4 Plus, CI-4, CH-4
CF-4, CF, CF-2, CE, CD-II/SM**

Contact your CAM2 representative or CAM2 distributor for additional information.

**PRODUCT
BULLETIN**

**www.CAM2.COM
800-338-CAM2**

Revised 5/15/2010