

CAM2[®]
INTERNATIONAL, LLC

CAM2
SUPERPRO MAX

**CAM2 SUPERPRO MAX
SYNTHETIC BLEND 10W-30
Product Code # 642**



API SN-RC & ILSAC G-5 Certified

CAM2 SUPERPRO MAX Motor Oils are fully licensed to meet or exceed the latest automotive manufacturers' requirements of API SN and SN-RC. CAM2 SuperPro MAX 5W-20, 5W-30, and 10W-30 are fully licensed to meet and exceed ILSAC GF-5 requirements for use in passenger car, SUV and light duty truck gasoline engines. CAM2 SuperPro MAX Motor Oils show improved high temperature deposit control, oil consumption and fuel economy. CAM2 SuperPro MAX 5W-20 and 5W-30 are synthetic blend premium motor oils that provide better low temperature pumpability and protection.

CAM2 SuperPro MAX Motor Oils are premium quality motor oils formulated from selected superior base oils and advanced additive technology. CAM2 SuperPro MAX motor oils are the engine oils of choice for passenger cars, light trucks, powerboats, motorcycles, and other stationary and mobile equipment.

CAM2 SUPERPRO MAX Motor Oils, through the use of the highest quality base oils and Advanced Additive Technology, are formulated to provide the highest levels of equipment protection available. CAM2 SuperPro MAX Motor Oils provide:

- Excellent Fuel Economy
- Excellent volatility for low oil consumption
- Excellent protection from deposits at all operating temperatures
- Excellent cold-cranking capabilities

Contact your CAM2 representative or CAM2 distributor for additional information.

**PRODUCT
BULLETIN**

www.CAM2.COM
800-338-CAM2

- Excellent cold-cranking capabilities
- Excellent anti-wear, anti-foam, bearing corrosion and anti-rust protection

CAM2 SuperPro MAX motor oils meets all previous service classifications, i.e. API SM, SL, SJ, SH, SG, SF and ILSAC GF-4, GF-3, GF-2, etc.

CAM2 SuperPro MAX motor oils provide:

API Service SN

Advanced wear, varnish & sludge protection

Superior Synthetic Blend Protection against thermal breakdown (5W-20 & 5W-30)

Meets or exceeds API Resource Conserving (RC) standards (5W-20, 5W-30, 10W-30)

ILSAC GF-5 Certified (5W-20, 5W-30, 10W-30)

CAM2 SuperPro MAX Motor Oils are recommended for the following uses:

- When API licensed SN, SM, SL, SJ, SH, SG, SF, SE, SD or SC oils are required
When ILSAC GF-5, GF-4, etc are required (5W-20, 5W-30, & 10W-30)

CAM2 SuperPro MAX 5W-20 can be used when Ford WSS-M2C945-A is specified

CAM2 SuperPro MAX 5W-30 can be used when Ford WSS-M2C946-A is specified
Chrysler MS-6395S

CAM2 SuperPro MAX Motor Oils are available in 5 multi-viscosity grades to comply with most passenger car and light duty truck engine applications. Two single-viscosity grades are also available. Follow equipment manufacturer recommendations for specific applications.

- For GM Vehicles model years 2011 and after, see our CAM2 dexos1™ full synthetic motor oil.

Contact your CAM2 representative or CAM2 distributor for additional information.

**PRODUCT
BULLETIN**



INTERNATIONAL, LLC

CAM2 SUPERPRO MAX

SAE GRADE:	5W20	5W30	10W30	10W30	10W40	20W50	SAE 30	SAE 40
	Synthetic Blend	Synthetic Blend		Synthetic Blend				
PRODUCT CODE:	408	409	414	642	416	417	419	420
Viscosity cSt @40 oC:	49.21	63.01	68.23	68.23	105.68	153.05	86.11	123.33
cSt @100 oC:	8.59	10.57	10.49	10.49	15.26	18.29	11.11	13.97
Viscosity, SUS @ 210 oF:	54.38	61.25	60.96	60.96	78.95	91.29	63.18	73.89
Viscosity Index:	153	158	141	141	152	134	116	111
API Gravity:	32.78	33.01	31.51	31.51	31.74	29.77	29.97	29
Pour Point oF:	-48	-48	-42	-42	-42	-36	-33	-24
API RC *Resource Conserving*:	YES	YES	YES	YES	NO	NO	NO	NO
ILSAC GF-5 Certified:	YES	YES	YES	YES	NO	NO	NO	NO
Color API Licensed Service:	3 SN,SM, SL, SJ	3 SN,SM, SL, SJ	3 SN,SM, SL, SJ	3 SN,SM, SL, SJ	3 SN,SM, SL, SJ	3.5 SN,SM, SL, SJ	3.5 SN,SM, SL, SJ	3.5 SN,SM, SL, SJ
Contact your CAM2 representative or CAM2 distributor for additional information.								

PRODUCT BULLETIN