



CAM2 All Season Anti-wear Hydraulic 5W-20 Product Code # 148

CAM2 ALL SEASON ANTI-WEAR HYDRAULIC OIL is a very high viscosity index hydraulic oil for use in mobile and industrial equipment operated in a wide range of sub-arctic and temperate climates. This product meets API viscosity 5W-20. ALL SEASONS formulation offers superior shear stability performance.

CAM2 ALL SEASON AW HYDRAULIC OIL is a premium anti-wear hydraulic fluid with outstanding low temperature characteristics. It is specially formulated for use in mobile equipment hydraulic circuits where wide temperature ranges are encountered. (Cherry pickers, bucket trucks and marine hydraulics).

It also can be used for traditional in-plant hydraulic applications, and exceeds most industry hydraulic fluid specifications, including: Denison HF-2, HF-0 Commercial Shearing, Vickers, Sunstrand, Rexnord, Cincinnati Milacron

TYPICAL PROPERTIES

ISO Viscosity	46
Viscosity @ cSt@40C	41.05
Viscosity @ cSt @ 100C	7.68
Viscosity Index	159
Pour Point, E F	-45
Flash Point, EF	390
Oxidation Test Hours to 2.0 acid number	2500+
Low Temperature Pumpability	Pass
Dielectric, min. KV	+35
Rust Test	Pass

Contact your CAM2 representative or CAM2 distributor for additional information.

PRODUCT BULLETIN

www.CAM2.COM
800-338-CAM2

Revised 11/18/2010