

CAM2 ULTRA 580 EP#2 w/5% MOLY**SECTION 1: PRODUCT AND COMPANY IDENTIFICATION****PRODUCT NAME:** CAM2 Ultra 580 EP #2 w/5% Moly**SYNONYMS:** Calcium sulfonate complex grease.**PRODUCT CODE:** 267**PRODUCT USE:** Industrial and automotive petroleum lubricating grease.**MANUFACTURER'S NAME:** CAM2 International, LLC**ADDRESS:** P.O. Box 1119
Evergreen, CO 80437
Tel: 800-338-2262**EMERGENCY TELEPHONE NUMBER:**
*These numbers are for emergency use only.
If you desire non-emergency product information,
please call phone number listed below.***UNITED STATES:** 1 800 633 8253
INTERNATIONAL: 1 801 629 0667**CUSTOMER SERVICE:** 303-292-0595**MSDS FORM NUMBER:** 267**SECTION 2: HAZARDS IDENTIFICATION****EMERGENCY OVERVIEW****APPEARANCE**

Gray/black, semi solid grease, slight petroleum odor.

CAUTION!**HEALTH HAZARDS**

Excessive exposure may result in eye, skin or respiratory irritation.

High-pressure injection under skin may cause serious damage.

HMIS Rating: Health: 1 Flammability: 1 Reactivity: 0

POTENTIAL HEALTH EFFECTS**Note:** This material should not be used for any other purpose than the intended use listed in Section 1 without expert advice. Health studies on similar products have indicated that chemical exposure may cause potential human health risks which may vary from person to person.**INHALATION (BREATHING):** This product is not likely to present an inhalation hazard at normal temperatures and pressures. However, when aerosolizing, misting, or heating of this product, high concentrations of generated vapor or mist may irritate the respiratory tract (nose, throat, and lungs).

CAM2 ULTRA 580 EP#2 w/5% MOLY

EYES: Excessive exposure may cause irritation.

SKIN: May cause irritation. Not likely to be absorbed through the skin in harmful amounts.

INGESTION (SWALLOWING): May be harmful if swallowed. May cause throat irritation, nausea, vomiting, and diarrhea. Breathing product into the lungs during ingestion or vomiting may cause lung injury and possible death.

MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE: Individuals with pre-existing respiratory tract (nose, throat, and lungs) eye and/or skin disorders may have increased susceptibility to the effects of exposure.

CHRONIC: Prolonged or repeated inhalation of oil mist may cause oil pneumonia, lung tissue inflammation, and/or fibrous tissue formation. Prolonged or repeated eye contact may cause inflammation of the membrane lining the eyelids and covering the eyeball (conjunctivitis). Prolonged or repeated skin contact may cause drying, cracking, redness, itching, and/or swelling (dermatitis).

POTENTIAL ENVIRONMENTAL EFFECTS: This product is not expected to be harmful to aquatic organisms.

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

Wt. Percent	Component	Synonym	CAS #
0 - 60	Distillates, petroleum, solvent-refined heavy paraffinic	Petroleum oil	64742-88-4
0 - 45	CSC Thickener	Not Available	Mixture
0 - 15	Severely Solvent Refined Residuum	Bright Stock	64742-01-4
0 - 15	Calcium carbonate	Not Available	1317-65-3
0 - 8	Molybdenum disulfide	Not Available	1317-33-5
< 1	Alkylated diphenylamine	Not Available	68608-27-5

SECTION 4: FIRST AID MEASURES

INHALATION (BREATHING): Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Oxygen should only be administered by qualified personnel. Someone should stay with victim. Get medical attention if breathing difficulty persists.

EYE: If irritation or redness from exposure to vapor develops, move away from exposure into fresh air. Upon contact, immediately flush eyes with plenty of lukewarm water, holding eyelids apart, for 15 minutes. Get medical attention.

CAM2 ULTRA 580 EP#2 w/5% MOLY

SKIN: Remove affected clothing and shoes. Wash skin thoroughly with soap and water. Get medical attention if irritation or pain develops or persists. If product is injected under pressure into or under the skin, or into any part of the body, regardless of the appearance of the wound or its size, a physician should immediately evaluate the individual as a medical emergency.

**INGESTION:
(SWALLOWING)** Do NOT induce vomiting. Immediately get medical attention. If spontaneous vomiting occurs, keep head below hips to avoid breathing the product into the lungs. Never give anything to an unconscious person by the mouth.

**NOTE TO
PHYSICIANS:** Treat symptomatically and supportively. Treatment may vary with condition of victim and specifics of incident.

SECTION 5: FIRE FIGHTING MEASURES
--

FLASH POINT (METHOD USED): 455°F (235°C) (minimum) (COC)

FLAMMABLE LIMITS IN AIR: Lower: Not Available Upper: Not Available

**AUTOIGNITION
TEMPERATURE:** Not established.

**HAZARDOUS COMBUSTION
PRODUCTS:** Decomposition and combustion materials may be toxic. Burning may produce sulfur oxides, aldehydes, ketones, oxides of carbon and unidentified organic compounds.

**CONDITIONS OF
FLAMMABILITY:** Sparks or flame. Product may burn, but does not ignite readily.

EXTINGUISHING MEDIA: Carbon dioxide, regular foam, dry chemical, water spray or water fog. Water or foam may cause frothing.

**INAPPROPRIATE
EXTINGUISHING
MEDIA:** Water stream may splash burning liquid and spread fire.

HAZARD RATING

0= LEAST
1= SLIGHT
2= MODERATE
3= HIGH
4= EXTREME

NFPA 704 HAZARD IDENTIFICATION

HEALTH HAZARD (BLUE)	1
FIRE HAZARD (RED)	1
REACTIVITY (YELLOW)	0
SPECIFIC HAZARD (WHITE)	

**PROTECTIVE EQUIPMENT
FOR FIRE FIGHTERS:** A positive-pressure, self-contained breathing apparatus (SCBA) and full-body protective equipment are required for fire emergencies.

FIRE FIGHTING INSTRUCTIONS: Keep storage containers cool with water spray.

**FIRE AND EXPLOSION
HAZARDS:** Heated containers may rupture. "Empty" containers may retain residue and can be dangerous. Product is not sensitive to mechanical impact or static discharge.

CAM2 ULTRA 580 EP#2 w/5% MOLY**SECTION 6: ACCIDENTAL RELEASE MEASURES**

Remove all ignition sources. Do not touch or walk through spilled product. Stop leak if you can do it without risk. Wear protective equipment and provide engineering controls as specified in **Section 8: EXPOSURE CONTROLS/ PERSONAL PROTECTION**. Isolate hazard area. Keep unnecessary and unprotected personnel from entering. Ventilate area and avoid breathing vapor or mist. Contain spill away from surface water and sewers. Contain spill for possible recovery, or sorb with compatible sorbent material and shovel with a clean spark-proof tool into a sealable container for disposal. Additionally, for large spills: Dike far ahead of liquid spill for collection and later disposal.

SECTION 7: HANDLING AND STORAGE**HANDLING:**

Keep away from sparks or flame. Where flammable mixtures may be present, equipment safe for such locations should be used. Use clean tools. When transferring large volumes of product, metal containers, including trucks and tank cars, should be grounded and bonded. This product has a low vapor pressure and is not expected to present an inhalation hazard under normal temperatures and pressures. However, when aerosolizing, misting, or heating this product, do not breathe vapor or mist. Use in a well ventilated area. Avoid contact with eyes, skin, clothing and shoes.

SHIPPING AND STORING:

Keep container tightly closed when not in use and during transport. Avoid excessive long-term storage temperatures to prolong shelf life. Maximum storage temperature: 120°F. Store product in well ventilated areas. Do not pressurize, cut, weld, braze, solder, drill, or grind containers. Keep containers away from flame, sparks, static electricity, or other sources of ignition. Empty product containers may retain residue and can be dangerous.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION**EXPOSURE GUIDELINES****Component Exposure Limits****Distillates, petroleum, solvent-refined heavy paraffinic (64742-88-4)**

ACGIH:	5mg/m ³ TWA (related to paraffin oils) 10 mg/m ³ STEL (related to paraffin oil)
OSHA Final:	5 mg/m ³ TWA (related to oil mist, mineral)
OSHA Vacated:	5 mg/m ³ TWA (related to oil mist, mineral)
NIOSH:	5 mg/m ³ TWA (related to oil mist, mineral) 10 mg/m ³ STEL (related to oil mist, mineral)

Exposure limits/standards for materials that can be formed when handling this product:

When mists/aerosols can occur, the following are recommended: 5 mg/m³ – ACGIH TLV, 10 mg/m³ – ACGIH STEL, 5 mg/m³ – OSHA PEL.

ENGINEERING CONTROLS:

Provide general ventilation needed to maintain concentration of vapor or mist below applicable exposure limits. Where adequate general ventilation is unavailable, use process enclosures, local exhaust ventilation, or other engineering controls to control airborne levels below applicable exposure

CAM2 ULTRA 580 EP#2 w/5% MOLY
limits.

PERSONAL PROTECTIVE EQUIPMENT

RESPIRATORY PROTECTION: No respiratory protection is normally required. Use NIOSH-certified P- or R-series particulate filter and organic vapor cartridges when concentration of vapor or mist exceeds applicable exposure limits. Protection provided by air purifying respirators is limited. Do not use N-rated respirators. Selection and use of respiratory protective equipment should be in accordance in the USA with OSHA General Industry Standard 29 CFR 1910.134; or in Canada with CSA Standard Z94.4. Consult a qualified Industrial Hygienist or Safety Professional for respirator selection guidance.

EYE PROTECTION: Where eye contact is likely, wear safety glasses or goggles; contact lens use is not recommended.

SKIN PROTECTION: Where skin contact is likely, wear neoprene, nitrile or equivalent protective gloves; use of natural rubber or equivalent gloves is not recommended. When product is heated and skin contact is likely, wear heat-insulating gloves, boots, and other protective clothing.

To avoid prolonged or repeated contact where spills and splashes are likely, wear appropriate chemical-resistant face shield, boots, apron, coveralls, long sleeve shirts, or other protective clothing.

PERSONAL HYGIENE: Use good personal hygiene. Wash thoroughly with soap and water after handling product and before eating, drinking, or using tobacco products. Clean affected clothing, shoes, and protective equipment before reuse. Discard leather articles, such as shoes, saturated with these products.

OTHER PROTECTIVE EQUIPMENT: Where spills and splashes are likely, facilities storing or using these products should be equipped with emergency eyewash and shower, both equipped with clean water, in the immediate work area.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES
--

PHYSICAL STATE, APPEARANCE	Semi-solid, gray/black
ODOR:	Slight petroleum odor
ODOR THRESHOLD:	Not available
MOLECULAR WEIGHT:	Not applicable
SPECIFIC GRAVITY:	0.99 (Estimated) (water=1) (approximately)
VAPOR DENSITY:	< 1 mm (Air = 1)
VAPOR PRESSURE:	less than 1 mm Hg at 77°F (25°C)
RELATIVE DENSITY:	0.99 g/cm ³ at 60°F (15.5°C)

CAM2 ULTRA 580 EP#2 w/5% MOLY

INITIAL BOILING POINT:	Not available
BOILING RANGE	Not established
FREEZING/MELTING POINT:	Not available
pH:	Not applicable
EVAPORATION RATE:	Not established
SOLUBILITY IN WATER:	Slight
FLASH POINT:	455°F (235°C) (minimum) Cleveland Open Cup
FLAMMABILITY:	Not available (does not ignite readily)
FLAMMABLE LIMITS IN AIR:	LOWER: Not available UPPER: Not available
AUTOIGNITION TEMPERATURE:	Not established

SECTION 10: STABILITY AND REACTIVITY

STABILITY:	Stable under normal temperatures and pressures.
INCOMPATIBILITY:	Avoid strong oxidizing agents.
REACTIVITY:	Polymerization is not known to occur under normal temperatures and pressures. Not reactive with water.
CONDITIONS TO AVOID:	Excessive heat and sources of ignition (open flame).
HAZARDOUS DECOMPOSITION PRODUCTS:	None under normal temperatures and pressures. Also see Section 5: HAZARDOUS COMBUSTION PRODUCTS.

SECTION 11: TOXICOLOGICAL INFORMATION

ROUTES OF EXPOSURE:	Exposure will most likely occur through skin contact or from inhalation of mechanically or thermally generated oil mist.
ACUTE EFFECTS:	May be harmful if swallowed. May irritate eyes and skin. May cause throat irritation, nausea, vomiting and diarrhea. Aspiration hazard: breathing product into the lungs during ingestion or vomiting may cause lung injury and possible death.
REPEATED DOSE EFFECTS:	Prolonged or repeated inhalation of oil mist may cause oil pneumonia, lung tissue inflammation, and/or fibrous tissue formation. Prolonged or repeated eye contact may cause inflammation of the membrane lining the eyelids and covering the eyeball (conjunctivitis). Prolonged or repeated skin contact may cause drying, cracking, redness, itching, and/or swelling

CAM2 ULTRA 580 EP#2 w/5% MOLY
(dermatitis).**SENSITIZATION:** Based on best current information, there is no known human sensitization associated with this product.**MUTAGENICITY:** No information available for this product.**CARCINOGENICITY** Based on best current information, there is no known carcinogenicity as regulated by OSHA; as categorized by ACGIH A1 or A2 substances; as categorized by IARC Group 1 Group 2A, or Group 2B agents as either known carcinogens or substances for which there is limited evidence of carcinogenicity in humans or sufficient evidence of carcinogenicity in experimental animals.**REPRODUCTIVE TOXICITY:** No information available for this product.**TERATOGENICITY:** No information available for this product.**NEUROTOXICITY:** No information available for this product.**TOXICITY DATA:****Component Analysis – LD50/LC50****Petroleum distillates, solvent-refined heavy paraffinic (64742-88-4)**

Inhalation LC50 Rat 2.18 mg/L 4 h

Oral LD50 Rat >5000 mg/kg

Dermal LD50 Rabbit >2000 mg/kg

SECTION 12: ECOLOGICAL INFORMATION**ECOTOXICITY:** Material is not expected to be harmful to aquatic organisms.**Component Analysis – Ecotoxicity – Aquatic Toxicity****Petroleum distillates, solvent-refined heavy paraffinic (64742-88-4)****Test & Species**

96 Hr LC50 Oncorhynchus mykiss - >5000 mg/L

PERSISTENCE/ DEGRADABILITY: Not determined.**BIOACCUMULATIVE POTENTIAL:** No information available for the product.**MOBILITY IN ENVIRONMENTAL MEDIA:** Base oil component(s) – Low solubility and floats; expected to migrate from water to the land. Expected to partition to sediment and wastewater solids.**OTHER ADVERSE EFFECTS:** Not available.**OCTANOL/WATER PARTITION** Not available.

**CAM2 ULTRA 580 EP#2 w/5% MOLY
COEFFICIENT:**

VOLATILE ORGANIC Not available.

COMPOUNDS:

AQUATIC RELEASE: Advise authorities if product has entered or may enter watercourses or sewer drains.

SECTION 13: DISPOSAL CONSIDERATIONS

DISPOSAL: Dispose in accordance with federal, state, provincial, and local regulations. Regulations may also apply to empty containers. The responsibility for proper waste disposal lies with the owner of the waste.

**USEPA WASTE
CODES:** This product, if discarded, is not expected to be a characteristic or listed hazardous waste. If recycled in the USA, it must be managed in accordance with 40 CFR Part 279. Processing, use, or contamination by user may change the waste code(s) applicable to the disposal of this product.

SECTION 14: TRANSPORT INFORMATION

**LAND (DOT):
(Shipping Name)** Not regulated as a hazardous material for Land Transport.

**LAND (TDG):
(Shipping Name)** Not regulated as a dangerous good for Land Transport.

**EMERGENCY RESPONSE
GUIDE NUMBER:** Not applicable
Reference *North American Emergency Response Guidebook*.

SECTION 15: REGULATORY INFORMATION

**OSHA Hazard
Communication
Standard:** When used for its intended purposes, this material is not classified as hazardous in accordance with OSHA 29 CFR 1910.1200.

**SARA SECTIONS
302, 304** Based on the ingredients listed in **SECTION 3**, this product does not contain any "extremely hazardous substances" listed pursuant to Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA) Section 302 or Section 304 as identified in 40 CFR Part 355, Appendix A and B.

**SARA SECTIONS
311 AND 312
REPORTING** This product poses the following health hazard(s) as defined in 40 CFR Part 370 and is subject to the requirements of sections 311 and 312 of Title III of Superfund Amendments and Reauthorization Act of 1986 (SARA):

Immediate (Acute) Health Hazard	No
Delayed (Chronic) Health Hazard	No
Physical Fire	No
Physical Sudden Release of Pressure	No

CAM2 ULTRA 580 EP#2 w/5% MOLY

Physical Reactive

No

**SARA SECTION
313**

This product contains no chemicals subject to the supplier notification requirements of the SARA 313 Toxic Release Program.

CERCLABased on the ingredients listed in **SECTION 3**, this product does not contain any "hazardous substances" listed pursuant to the Comprehensive Environmental Response, Compensation and Liability Act of 1980 (CERCLA) in 40 CFR Part 302, Table 302.4.**TSCA:**

This product is in compliance with the Toxic Substances Control Act (154USC2601-2629).

SECTION 16: OTHER INFORMATION**DATE ISSUED:**

July 26, 2010

SUPERSEDES:

January 05, 2009

REVISION NO.

3

REVISION INFORMATION:

MSDS update adding additional Globally Harmonized System (GHS) requirements.

LABEL/OTHER INFORMATION:

Not available.

MSDS FORM NUMBER: 267

The information in this Safety Sheet was obtained from sources which we believe are reliable. HOWEVER, THE INFORMATION IS PROVIDED WITHOUT ANY WARRANTY, EXPRESS OR IMPLIED, REGARDING ITS CORRECTNESS. The conditions or methods of handling, storage, use and disposal of the product are beyond our control and may be beyond our knowledge. FOR THIS AND OTHER REASONS, WE DO NOT ASSUME RESPONSIBILITY AND EXPRESSLY DISCLAIM LIABILITY FOR LOSS, DAMAGE OR EXPENSE ARISING OUT OF OR IN ANY WAY CONNECTED WITH THE HANDLING, STORAGE, USE OR DISPOSAL OF THE PRODUCT. This safety sheet was prepared and is to be used only for this product. If the product is used as a component in another product, this safety sheet information may not be applicable.

-END OF DOCUMENT-