



**CAM2 Mining
Hydraulic 68 Fluid
Product Code #149**

CAM2 Mining Hydraulic 68 Fluid is a quality anti-wear hydraulic oil providing excellent anti-wear, rust and oxidation protection.

APPLICATIONS

CAM2 Mining Hydraulic 68 Fluid may be recommended for applications when a quality, anti-wear hydraulic oil is required by equipment manufacturers.

CAM2 Mining Hydraulic 68 Fluid provides excellent vane pump wear and protection. Extremely low pump part weight losses were encountered in the ASTM-D-2882 Vane Pump Wear Tests.

CAM2 Mining Hydraulic 68 Fluid is available in square metal 35 pound tins approved for underground mining applications.

FEATURES:

- **CAM2 Mining Hydraulic 68 Fluid** contains additive systems which impart characteristics desired in these types of oils:
- Thermal stability - **CAM2 Mining Hydraulic 68 Fluid** contain thermally stable zinc-type additives.
- Provides rust protection
- Excellent anti-wear protection to pumps, motors, valves, and other hydraulic circuit components.
- Provides antifoam protection
- Hydraulic stability in the presence of water - will not contribute to the formation of corrosive reactants or metal-etching acids.

Contact your CAM2 representative or CAM2 distributor for additional information.

**PRODUCT
BULLETIN**

**www.CAM2.COM
800-338-CAM2**

CAM2 Mining Hydraulic 68 Fluid

Typical Properties:

PRODUCT CODE	149
ISO Viscosity Grade	68
Viscosity, cSt 40C (104F)	68
Flash, °F	455
Fire, °C	510
Color, ASTM D1500	2.5
Zinc (Ppm)	>150
Rust Prev. Test	PASSES

Contact your CAM2 representative or CAM2 distributor for additional information.

**PRODUCT
BULLETIN**

**www.CAM2.COM
800-338-CAM2**

Revised 5/15/2010