



## PRODUCT BULLETIN

# SuperHD Premium Plus (07) 15W-40

*API CJ-4/SN/CI-4 Plus*

PRODUCT #333

**CAM2 SuperHD Premium Plus (07) 15W-40** through the use of premium quality Group II & Group III base stocks and advanced additive technology is formulated to provide the highest levels of equipment protection available in Cummins, Volvo, Mack, Caterpillar, Detroit Diesel, and all other Heavy Duty applications calling for a CJ-4 engine oil.

**CAM2 SuperHD Premium Plus (07) 15W-40** is synthetic blend engine oil with next generation soot control. CAM2 SuperHD Premium Plus (07) 15W-40 meets and exceeds the latest API CJ-4/SN, Cummins CES 20081, Volvo VDS-4, Mack EO-O Premium Plus (07), Caterpillar ECF-3, and Detroit Fluids Specification 93K218

**CAM2 SuperHD Premium Plus (07) 15W-40** is a synthetic blend, heavy-duty multi-grade oil for all-season use in diesel powered or a mix of gasoline and diesel powered equipment. It meets or exceeds the warranty and service requirements of virtually all diesel and gasoline engine manufactures. It can be recommended for both newer and older engines.

**CAM2 SuperHD Premium Plus (07) 15W-40** is especially designed for today's high-performance, low-emissions diesel engines, equipped with Exhaust Gas Recirculation (EGR) and Diesel Particulate Filters.

**CAM2 SuperHD Premium Plus (07) 15W-40** carries the following OEM Approvals

- CES 20080
- DFS93K218
- Mack EO-O
- Volvo VDS-4

Applications continued on pg 2.

## FEATURES

**CAM2 SuperHD Premium Plus (07) 15W-40** provides:

- Excellent protection from deposits at all operating temperatures
- Excellent bearing corrosion protection (EGR critical)
- Excellent anti-wear properties
- Excellent anti-foam properties
- Excellent anti-rust properties
- Excellent soot control
- Extended drain capable
- Broad range of OEM approvals



**CAM2 INTERNATIONAL, LLC**

211 Violet Street Suite 100 • Golden, CO 80401

Telephone 800/338-2262 • Fax: 303/679-8988

[www.CAM2.com](http://www.CAM2.com)



## PRODUCT BULLETIN

# SuperHD Premium Plus (07) 15W-40

API CJ-4/SN/CI-4 Plus

PRODUCT #333

### APPLICATIONS

- When CJ-4, CI-4 PLUS, CI-4, CH-4, CG-4, CF-4, CF, CF-2 oils are required
- When SN, SM, SL, SJ, SH, SG, SF oils are required
- When a US Military CID A-A-52306 performance level is required
- Meets the performance requirements of MIL-L-2104H
- ACEA E5-02, JASO DHD-1, GLOBAL DHD-1
- When GM 4718M/6094M and Ford M2C153-E oils are required
- In all diesel and gasoline engines, including turbo-charged models
- When Detroit Fluid Specification is required
- In Caterpillar engines ECF-3
- In Mack engines EO-O PREMIUM PLUS (07) approval, EO-N PREMIUM PLUS, EO-M Plus, EO-M, EO-L Plus, EO-L, EO-K/2
- In Cummins engines CES 20071, 20076, 20077, 20078, 20081
- In Volvo VDS-4, VDS-3, VDS-2 and VDS engines
- In Caterpillar drive trains TO- 32
- When Allison C-3/C-4 fluids are required
- Mercedes Benz MB 228.5, 228.3

### TECHNICAL DATA

Product Code	333
API Gravity	30
Viscosity @ 40°C, cSt	111
Viscosity @ 100°C, cSt	15.5
Viscosity Index	146
Pour Point: °C	-32
Flash Point: °C	231
Borderline Pumping, °C	-20
Sulfated Ash wt%	1
Total Base Number	10
API Licensed Service:	CJ-4, CI-4 Plus, CI-4, CH-4, CF-4, CF, CF-2, CE, CD-II/SN

Contact your CAM2 representative or CAM2 distributor for additional information.

#### CAM2 INTERNATIONAL, LLC

211 Violet Street Suite 100 • Golden, CO 80401

Telephone 800/338-2262 • Fax: 303/679-8988

www.CAM2.com