



PRODUCT BULLETIN

PROMAX R&O Hydraulic Oil

PRODUCT # 147

PROMAX R & O Hydraulic Oil is blended from highly-refined base stocks to provide outstanding lubricating properties in a wide-range of applications. It is formulated with select additives to provide excellent anti-rust, anti-oxidation, anti-corrosion and anti-foam performance.

Features

CAM 2 PROMAX R & O Hydraulic Oil

- Protection against oxidation
- Protection against rust and corrosion
- Low foaming

Applications

PROMAX R & O Hydraulic Oil is suitable for use in the following applications:

- Applications where a straight mineral oil is required without extreme pressure (EP), detergent, dispersant or anti-wear additives.
- General machine oil
- Low pressure circulating fluid
- Non-Critical hydraulic applications
- Air-tool oil
- Drip or splash lubricant
- Spindle Oil
- Lubrication of light-duty compressors

Typical Characteristics

R&O Hydraulic Oil	Test Method	
Product Code		147
API Gravity, 60° F	ASTM D-1298A	28.0
Viscosity, cSt @ 40°C	ASTM D-445	41-50
Approx. ISO Grade	ASTM D-2270	46
Pour Point, °C (°F)	ASTM 5949	-29 (-20)
Flash Point,(°C)	ASTM D-92	226
Color	ASTM D-1500	2.0 max
Oxidation Life Hrs to 2.0 Acid No	ASTM 943	2500

The above characteristics are typical of current production. While production will conform to CAM2's specification, slight variations may occur and do not affect performance.

Special Handling, Notices, or Warnings

Avoid contact with skin. Rinse with soap and water immediately after skin contact. This product is unlikely to present and significant health hazards. Dispose of used oil properly.

For more information, contact your CAM2 Representative or visit our website @ www.CAM2.com

CAM2 INTERNATIONAL, LLC

211 Violet Street Suite 100 • Golden, CO 80401 Telephone 800/338-2262 • Fax: 303/679-8988
www.CAM2.com