



PRODUCT BULLETIN

Blue Blood Elite Full Synthetic Motor Oil 0W-30

API SN

PRODUCT #402

CAM2 BLUE BLOOD ELITE FULL SYNTHETIC MOTOR OIL with Engine DETOX, Fast Action Additives is the premium choice for preventative maintenance in vehicles that operate under severe driving and temperature conditions. It is designed to provide quick flow to critical parts in high RPM engines that experience extreme heat. It can be used in virtually all services for all gasoline engines, domestic and foreign. It is fully compatible with virtually all other synthetic and petroleum based engine oils.

CAM2 BLUE BLOOD ELITE FULL SYNTHETIC MOTOR OIL provides the ultimate protection against wear, sludge/deposit build-up, while improving fuel economy. CAM2 Blue Blood ELITE Full Synthetic Motor Oil meets or exceeds API SN. It is suitable for passenger cars, light trucks, powerboats, and other stationary and mobile equipment that require API licensed SN, SM, SL, SJ, SF, etc.

FEATURES

- Excellent protection from deposits at all operating temperatures.
- Excellent anti-wear, anti-foaming, anti-rust and corrosion protection
- Excellent cold cranking capabilities
- Excellent protection against accelerated oil consumption

APPLICATIONS

CAM2 Blue Blood ELITE Full Synthetic Motor Oil 0W-30, may be recommended for the following uses:

- When SN, SM, SL, SJ, SH, SG, SF, SE, SD or SC oils are required
- When former MIL-L-46152D oil performance level is required
- GM 6094M

See Technical Data on pg 2.



CAM2 INTERNATIONAL, LLC

685 Haining Road, Vicksburg, MS 39183 USA • Tel: 800-338-2262

www.CAM2.com



PRODUCT BULLETIN

Blue Blood Elite Full Synthetic Motor Oil 0W-30

API SN

PRODUCT #402

TYPICAL PROPERTIES

SAE GRADE	0W-20	5W-20	0W-30	5W-30	10W-30	0W-40	5W-40
Product Code	365	960	402	961	962	405	382
Density, lb/gal	7.1	7.2	7.10	7.12	7.11	7.07	7.14
API Gravity	35.52	34.95		34.85	34.04	35.72	33.65
CCS, mPa/s	6100	3900	5500	3900	4000	6100	6200
Viscosity @ 40°C, cSt	44.5	47.57	56.49	60.48	63.72	85.43	93.74
Viscosity @100°C, cSt	8.46	8.55	10.44	10.42	10.29	14.93	15.02
Viscosity Index	170	159	177	162	149	184	170
NOACK	13.1	13.8	13.5	12.0	11.0	12.9	12.0
Color ASTM	2.5	3	3	3	3	3	3
Appearance	Clear	Clear	Clear	Clear	Clear	Clear	Clear
Pour Point:°C	-48	-45	-48	-45	-42	-50	-42
Flash Point:°C	216	225	200	240	250	210	220

Contact your CAM2 representative or CAM2 distributor for additional information.

CAM2 INTERNATIONAL, LLC

685 Haining Road, Vicksburg, MS 39183 USA • Tel: 800-338-2262

www.CAM2.com