



## PRODUCT BULLETIN

# PROTECT75 High Mileage Synthetic Blend 5W-30 Motor Oil

*API SN, ILSAC GF-5*

PRODUCT #693

**CAM2 PROTECT75 HIGH MILEAGE 5W-30 Motor Oil** is formulated to meet the requirements of higher mileage engines. As your engine ages and accumulates over 75,000 miles, problems such as oil consumption, oil leakage and lower cylinder compression may arise. Most modern engine oils are formulated to meet new car warranty requirements and are not specifically designed to address the needs of higher mileage engines, **CAM2 PROTECT75 HIGH MILEAGE 5W-30 Motor Oil** is designed for both.

**CAM2 PROTECT75 HIGH MILEAGE 5W-30 Motor Oils** contains specific additives targeted to counter the effects of high mileage on your engine. Higher mileage engines can experience spark plug fouling, excessive intake valve deposits and sludge build up which can lead to a loss of power and performance.

**CAM2 PROTECT75 HIGH MILEAGE Motor Oils** are specially blended engine oils that have a low volatility, which helps reduce oil consumption, special seal conditioning agents and premium additives for improved wear protection needed in new and high mileage engines.

## FEATURES

**CAM2 PROTECT75 HIGH MILEAGE Motor Oils advantage:**

- Conditions engine seals
- Minimizes oil consumption
- Maximizes power output
- Resists thermal breakdown
- Licensed API Service SN and ILSAC GF-5

See Technical Data on pg 2.



**CAM2 INTERNATIONAL, LLC**

211 Violet Street Suite 100 • Golden, CO 80401

Telephone 800/338-2262 • Fax: 303/679-8988

[www.CAM2.com](http://www.CAM2.com)



## PRODUCT BULLETIN

# PROTECT75 High Mileage Synthetic Blend 5W-30 Motor Oil

API SN, ILSAC GF-5

PRODUCT #693

### APPLICATIONS

CAM2 PROTECT75 HIGH MILEAGE Motor Oils may be recommended in the following applications:

- When SN, SM, SL, SJ, SH, SG, SF, SE, SD or SC oils are required
- CAM2 PROTECT75 HIGH MILEAGE Motor Oil 5W-20, 5W-30 and 10W-30 can be used when ILSAC GF-5, GF-4, GF-3, GF-2, GF-1 oils are required
- May be used in both old and newer passenger car engines
- CAM2 PROTECT75 HIGH MILEAGE Motor Oil 5W-20 can be used when Ford WSS-M2C945-A is specified
- CAM2 PROTECT75 HIGH MILEAGE Motor Oil 5W-30 can be used when Ford WSS-M2C946-A is specified
- Chrysler MS-6395S
- For GM Vehicles model years 2011 and after, see our CAM2 dexos1™ Generation 2 full synthetic motor oil.

### TECHNICAL DATA

SAE Grade	5W-20 Synthetic Blend	5W-30 Synthetic Blend	10W-30 Synthetic Blend	10W-40 Synthetic Blend
PRODUCT CODE:	696	693	697	698
Viscosity cSt @ 40°C:	49.21	63.01	68.23	105.68
cSt @ 100°C:	8.59	10.57	10.49	15.26
Viscosity, SUS @ 210°F:	54.38	61.25	60.96	73.89
Viscosity Index:	153	158	141	152
API Gravity:	32.78	33.01	31.51	31.74
Pour Point °F:	-48	-48	-42	-42
API: RC *Resource Conserving*:	YES	YES	YES	NO
ILSAC GF-5 Certified:	YES	YES	YES	NO
API Licensed Service:	SN,SM,SL, SJ ILSAC GF-5	SN,SM,SL, SJ ILSAC GF-5	SN,SM,SL, SJ ILSAC GF-5	SN,SM, SL,SJ

Contact your CAM2 representative or CAM2 distributor for additional information.

#### CAM2 INTERNATIONAL, LLC

211 Violet Street Suite 100 • Golden, CO 80401

Telephone 800/338-2262 • Fax: 303/679-8988

www.CAM2.com