

## PRODUCT BULLETIN

# CAM2 Industrial EP Gear Oils

Product #: 515, 516, 517, 518, 519, 520, 521

**CAM2 Industrial EP Gear Oils** are premium quality, extreme pressure gear oils for use in industrial service. These lubricants have good oxidation and thermal stability, are noncorrosive to gear and bearing materials, provide excellent rust protection, and resist oil thickening and deterioration for long service life. Exhibits excellent demulsibility and non-foaming characteristics during field trials..

**CAM2 Industrial EP Gear Oils** are designed for use in conditions of high temperature and extreme pressure including enclosed gear systems, such as spur, bevel, herringbone, worm, and hypoid gears, chain drives, sprockets, slide guides and ways, and bearing sets. Misting oils and rock drill oils are other applications for these products. These fluids satisfy the requirements of U.S. Steel 224, AGMA 250.04, AGMA 251.02, and API GL-1 through GL-5 specifications.

### TYPICAL PROPERTIES

Product Code	515	516	517	518	519	520	521
ISO Grade	68	100	150	220	320	460	680
AGMA Number	2EP	3EP	4EP	5EP	6EP	7EP	8EP
Viscosity @ 40°C, cSt	68	100	150	218	316	456	676
Viscosity @ 100°C, cSt	8.6	11.3	14.8	19	24.3	30.7	45.6
Viscosity Index	98	98	98	98	98	98	115
Flash Point, °C	258	260	261	265	269	272	276
Pour Point, °C	-25	-23	-20	-17	-14	-12	-9
Specific Gravity @ 60°F	0.886	.890	0.892	0.893	0.895	0.896	0.899
Timken	65	65	65	65	65	65	65
Copper Corrosion	1b	1b	1b	1b	1b	1b	1b