



## PRODUCT BULLETIN

### Concrete Form Oil

PRODUCT #179

**CAM2 CONCRETE FORM RELEASE OIL** is a low viscosity ready to use form release oil. Formulated to prevent bonding steel/wood forms and concrete surfaces, a special additive package allows it to also be used on Teflon coated forms, as well as mold surfaces generally used in concrete pre-cast operations. CAM2 Concrete Form Oil improves the stripping of forms, and extends form life by protecting wood, and providing corrosion protection on metal forms.

#### FEATURES:

**CAM2 Form Release Oil contains additives which impart characteristics most desired in these types of oils:**

- Excellent low temperature properties
- Excellent rust and corrosion protection
- Excellent low misting properties
- Creates a positive barrier, preventing adherence of concrete
- Non-staining to most aggregates
- Applicable to multiple surfaces
- Easy clean up, leading to improved efficiencies
- Low odor

#### APPLICATIONS:

CAM2 Form Release Oil is recommended for use with wood, steel, plastic, aluminum, fiberglass, and fiber tube forms. CAM2 Form Release Oil can be applied by a variety of methods: including spraying, brushing, mopping, dipping or rolling.

#### TYPICAL PROPERTIES

Product Code	179
API Gravity	31.0
Viscosity @ 40°C	12.1 cSt
Flash Point. °F	184
Pour Point. °F	-40



**CAM2 INTERNATIONAL, LLC**

685 Haining Road, Vicksburg, MS 39183 USA • Tel: 800-338-2262  
www.CAM2.com