



## PRODUCT BULLETIN

### CAM2 SuperHD 10W-40 Synthetic Blend Engine Oil

API CJ-4/SN, CI-4 Plus

PRODUCT #217

**CAM2 SuperHD 10W-40 Engine Oil** is the premium choice for preventative maintenance in vehicles that operate under severe driving and temperature conditions. The advanced, low emissions, low-ash formulation of CJ-4 engine oil keeps both engines and after-treatment systems (including Diesel Particulate Filters) cleaner allowing for extended service operation in all driving conditions.

**CAM2 SuperHD 10W-40 Engine Oil** provides superior wear protection and oxidative resistance. The technologically advanced viscosity modifier has been molecularly engineered to resist shearing and reduces friction leading to longer engine life.

**CAM2 SuperHD 10W-40** is suitable for use in high output Detroit Diesel®, Cummins®, Mack®, Caterpillar® and Volvo® engines. It is suitable for most naturally aspirated or turbo-charged diesel engines as well as exhaust gas re-circulated engines used in truck or off-highway equipment.

**CAM2 SuperHD 10W-40** features a new "Low-SAPS" additive technology to exceed API CJ-4/SN, CI-4 Plus specifications providing exceptional performance, long drain interval capability, and protection of exhaust systems including those fitted with Diesel Particulate Filters (DPF).

The "Low-SAPS" additive technology allows **SuperHD 10W-40** to meet the requirements of ACEA-16 while being future proof to ACEA-18. Protective power is further enhanced by using a blend of low pour point synthetic and thermally stable hydrocracked base oils to deliver our most fuel efficient 10W-40 engine oil to date.

#### FEATURES

- Emission system friendly  
Pre vents premature DPF plugging and shortened maintenance inter als

- e  
elo
- De  
oou  
•
- I  
•  
Deuu
- ou  
o
- o  
•
- •  
Do
- •  
eouu

Applications on pg 2.

CAM2 INTERNATIONAL, LLC

685 Haining Road, Vicksburg, MS 39183 USA • Tel: 800-338-2262

www.CAM2.com



## PRODUCT BULLETIN

### **CAM2 SuperHD 10W-40 Synthetic Blend Engine Oil**

*API CJ-4/SN, CI-4 Plus*

PRODUCT #217

#### **APPLICATIONS**

- When CJ-4, CI-4 PLUS, CI-4, CH-4 oils are required
- When SN, SM, SL, SJ, oils are required
- ACEA E9-16
- JASO MA/MA2
- Cummins CES 20081
- MACK EO-O Premium Plus '07
- Deutz DQC III-05
- MTU Type 2.1
- DDC 93K218
- Renault VI RLD-3
- Caterpillar (ECF-3)
- MB 228.31
- Volvo VDS-4
- Ford WSS-W2C171-E
- MAN 3575

#### **TYPICAL PROPERTIES**

|                       |                    |
|-----------------------|--------------------|
| SAE GRADE             | <b>10W-40</b>      |
| Product Code          | 217                |
| API                   | CJ-4/SN, CI-4 Plus |
| Density               | 0.866              |
| Viscosity @100°C, cSt | 15.5               |
| Viscosity Index       | 150                |
| Total Base Number     | 10                 |
| Sulfated Ash, wt.%    | <0.8               |
| Pour Point:°C         | -38                |
| Flash Point:°C        | 230                |

The above characteristics are typical of current production. While production will conform to CAM2's specification, slight variations may occur and do not affect performance.

Always consult owners manual for proper viscosity and performance recommendations

**Contact your CAM2 representative or CAM2 distributor for additional information.**

**CAM2 INTERNATIONAL, LLC**

685 Haining Road, Vicksburg, MS 39183 USA • Tel: 800-338-2262  
www.CAM2.com