

PRODUCT BULLETIN

PROMAX™ 303 Tractor Hydraulic Oil

PRODUCT #167

CAM2 PROMAX™ Tractor Hydraulic 303 Oil is a general-purpose lubricant for farm and industrial tractors and construction equipment. **CAM2 PROMAX™ Tractor Hydraulic 303 Oil** provides performance in the areas of anti-wear, PTO clutch, rust protection, extreme pressure properties, water sensitivity, foam suppression and brake chatter reduction.

CAM2 PROMAX™ Tractor Hydraulic 303 Oil is recommended for ambient temperatures between +32°F and 104°F (0°C to 40°C). For ambient temperatures outside this range or where a premium tractor hydraulic/transmission oil is required, please use a CAM2 Premium Tractor Hydraulic Fluid. **CAM2 PROMAX™ Tractor Hydraulic 303 Fluid** is suitable as a replacement for the following manufacturers where a tractor hydraulic fluid of this performance level is recommended:

APPLICATIONS

Allis Chalmers®
 Allison®
 Caterpillar®
 Deutz®
 Ford® Tractor
 International Harvester®
 JI Case®/David Brown®
 John Deere® 303, J20A
 Kubota®
 Massey Ferguson®
 Oliver®
 White®

Misapplication may cause severe performance problems. CAM2 PROMAX™ Tractor Hydraulic 303 Fluid has not been recommended by any OEM for model years later than 1974. For equipment built after 1974 requiring multi-functional fluid, use a CAM2 J20A or CAM2 Premium Tractor Hydraulic Fluid.

See Technical Data on pg. 2.

TECHNICAL SPECIFICATIONS

Product Code	167
SAE Grade	20
Gravity, °API	30
Viscosity @ 40°C, cSt	40-68
Viscosity Index	61 min.
Flash Point, °C/°F	204/400
Pour Point, °C/°F	-17/0
Color (ASTM-D1500)	6 max.

