



PRODUCT BULLETIN

CAM2 4T PREMIUM OUTBOARD SAE 10W-40 MARINE ENGINE OIL

API SJ#7 : !&

PRODUCT # 330

CAM2 4T Premium Outboard Marine Engine Oil is a premium outboard engine oil formulated to meet the needs of most 4-stroke outboard marine engines. Developed for the rigors associated with operating in both fresh and saltwater environments, **CAM2 4T Outboard** outperforms automotive engine oils commonly employed in marine applications. Field testing has demonstrated acceptable performance in applications requiring use of a NMMA FC-W® engine oil.

CAM2 4T Premium Outboard Marine Engine Oil provides excellent wear and corrosion protection in low to medium horsepower four-stroke engines and are capable of extending both drain intervals and engine life in a properly maintained system. The high concentration of low-ash antioxidant and detergent additives reduce the accumulation of harmful performance-robbing carbon deposits by neutralizing the free radicals which thicken oil and reduce pumpability. It also includes a robust rust and corrosion inhibitor not found in regular non-marine engine oils which protect against the certain ingress of water.

CAM2 4T Premium Outboard Marine Engine Oil is fortified with a thermally, shear stable viscosity improver which minimizes oil consumption and extends fuel efficiency. The molybdenum disulfide anti-wear agent provides proven protection from cam wear allowing for use in **Mercuriser** engines.

By using a combination of mineral and synthetic base fluids, CAM 4T outboard is able to provide outstanding protection in both extreme hot and cold temperatures. The synthetic base stock eliminates wax crystallization in sub-freezing temperatures allowing for oil to be quickly pumped to all areas of the engine immediately upon ignition while the mineral base reduces volatility increasing cleanliness, maximizing wear protection, and resisting oil oxidation.

FEATURES/BENEFITS

- De
- Excellent
- U
- -
- h@K VU U ° 7# W
- Reduces engine deposits to help maximize engine response

APPLICATIONS

CAM2 4T Premium Outboard Engine Oil may be recommended for the following uses:

- In
- M VU U ° 7# † h@K #7
- Suitable for use in Honda, Yamaha, Suzuki, Mercury, Evinrude, Tohatsu, and most other four-stroke outboard engines
- Older model light-duty passenger cars, trucks, and vans requiring an API SJ/CF-2 engine oil

SPECIFICATIONS

- When API SJ/CF-2
- NMMA FC-W (non-licensed)

See Technical Data on pg 2.



PRODUCT BULLETIN

CAM2 4T PREMIUM OUTBOARD SAE 10W-40 MARINE ENGINE OIL

API SJ# : !&

PRODUCT # 330

TECHNICAL DATA

SAE GRADE	10W-40
Product Code	330
Viscosity @ 40°C, cSt	90.6
Viscosity @ 100°C, cSt	13.2
Viscosity Index	145
CCS @ -25°C	5800
NOACK	<22.0
Phosphorus, ppm	<800
EOFT	<50%

CAM2 4T Outboard Marine Engine Oil has been field tested and is formulated to meet the rigorous requirements of NMMA FC-W performance category. It is not officially licensed by NMMA and should not be used in warranty applications requiring the use of such fluids.

Contact your CAM2 representative or CAM2 distributor for additional information.

CAM2 INTERNATIONAL, LLC

211VioletStreetSuite100•Golden, CO80401

Telephone800/338-2262•Fax:303/679-8988

www.CAM2.com