

PRODUCT BULLETIN SYNAVEX™ Full Synthetic Motor Oil 0W-40

API SN

PRODUCT #993

CAM2 SYNAVEX™ 0W-40 is an advanced formula of 100% FULL SYNTHETIC fully licensed API SN multi-grade engine oils designed for vehicles operating under severe driving or extreme temperature conditions. Compared to conventional motor oils, they provided improved engine cleanliness and high temperature deposit protection. These products also help reduce oil consumption and provide exceptional cold flow properties.

Exceeds API Service SN

- Advanced Wear, Varnish & Sludge Protection
- Superior Protection Against Thermal Breakdown
- Improved Fuel Economy

CAM2 SYNAVEX™ 0W-40 is a premium quality; full synthetic engine oil formulated from selected superior base oils, shear stable viscosity improvers, and advanced high performance engine oil additive technology.

CAM2 SYNAVEX™ 0W-40 full synthetic engine oil is formulated with low friction additives to help improve fuel economy where SAE 0W-40 is recommended and to provide outstanding engine protection. CAM2 SYNAVEX™ engine oils are designed especially for turbo-charged and high RPM engines which experience high heat and they provide quick flow to critical parts at start up to reduce wear. CAM2 SYNAVEX™ is the engine oil of choice for passenger cars, light trucks, powerboats, motorcycles and other stationary and mobile equipment when en- gine life and performance are important. CAM2 SYNAVEX™ meets or exceeds the latest American Petroleum Institute (API) SN service classification. CAM2 SYNAVEX™ also meets all previous service classifications: API SM, SL, SJ, SH, SG, SF.

CAM2 SYNAVEX™ 0W-40 is designed especially for turbo-charged and high RPM engines which experience high heat. They provide quick flow to critical parts at start up to reduce wear. CAM2 SYNAVEX™ MOTOR OILS can be used in virtually all services for all gasoline engines, domestic and foreign. CAM2 SYNAVEX™ MOTOR OILS are fully compatible with all other synthetic and petroleum based engine oils.

See Technical Data on pg 2.

FEATURES

- Excellent protection from deposits at all operating temperatures
- Excellent anti-wear, anti-foaming, anti-rust and corrosion protection
- Excellent cold cranking capabilities
- Excellent protection against accelerated oil consumption





PRODUCT BULLETIN SYNAVEX™ Full Synthetic Motor Oil 0W-40

API SN PRODUCT #993

APPLICATIONS

CAM2 SYNAVEX™ 0W-40 may be recommended for the following uses:

- When SN, SM, SL, SJ, SH, SG, SF, SE, SD or SC oils are required
- ACEA A3/B4-16
- MS-12633 (0W-40), may also be used in SRT engines calling for MS-10725
- MB-229.3, MB-229.5
- Porsche A40
- VW 502.00/503.01/505.00
- Nissan Genuine Performances
- FIAT 9.55535-M2

TYPICAL PROPERTIES

SAE GRADE	0W-40
Product Code	993
Density, lb/gal	7.18
API Gravity	33.98
Cold Crank Simulation, mPa/s	5800
Viscosity @ 40°C, cSt	88.5
Viscosity @ 100°C, cSt	13.8
Viscosity Index	159
NOACK	<15%
Color ASTM	3
Water And Sediment (Pass/Fail)	Pass
Appearance	Clear
Pour Point: °C	-39
Flash Point: °C	255

Contact your CAM2 representative or CAM2 distributor for additional information.