



## PRODUCT BULLETIN

# SYNAVEX™ Full Synthetic Motor Oil 0W-40

API SN Plus

PRODUCT #993

**CAM2 SYNAVEX™ 0W-40** is an advanced formula of 100% FULL SYNTHETIC fully licensed API SN Plus multi-grade engine oils designed for vehicles operating under severe driving or extreme temperature conditions. It is specially formulated to prevent LSPi events in turbo-charged and gasoline direct inject engines. Synavex® 0W-40 also provides substantial gains in fuel economy with well maintained engines seeing up to a 3% increase in fuel economy.

**CAM2 SYNAVEX™ 0W-40** is a premium quality; full synthetic engine oil formulated from selected superior base oils, shear stable viscosity improvers, and advanced high performance engine oil additive technology.

**CAM2 SYNAVEX™ 0W-40** full synthetic engine oil is formulated with low friction additives to help improve fuel economy where SAE 0W-40 is recommended and to provide outstanding engine protection. **CAM2 SYNAVEX™** engine oils are designed especially for turbo-charged and high RPM engines which experience high heat and they provide quick flow to critical parts at start up to reduce wear. **CAM2 SYNAVEX™** is the engine oil of choice for passenger cars, light trucks, powerboats, motorcycles and other stationary and mobile equipment when engine life and performance are important. **CAM2 SYNAVEX™** meets or exceeds the latest American Petroleum Institute (API) SN Plus service classification. **CAM2 SYNAVEX™** also meets all previous service classifications: API SN, SM, SL, SJ, SH, SG, SF.

**CAM2 SYNAVEX™ 0W-40** is designed especially for turbo-charged and high RPM engines which experience high heat. They provide quick flow to critical parts at start up to reduce wear. **CAM2 SYNAVEX™ MOTOR OILS** can be used in virtually all services for all gasoline engines, domestic and foreign. **CAM2 SYNAVEX™ MOTOR OILS** are fully compatible with all other synthetic and petroleum based engine oils.

See Technical Data on pg 2.

## FEATURES

- Excellent protection from deposits at all operating temperatures
- Excellent anti-wear, anti-foaming, anti-rust and corrosion protection
- Excellent cold cranking capabilities
- Excellent protection against accelerated oil consumption
- Advanced Wear, Varnish & Sludge Protection
- Superior Protection Against Thermal Breakdown
- Improved Fuel Economy
- Eliminates LSPi events in TGDl and Turbo-charged engines



CAM2 INTERNATIONAL, LLC

685 Haining Road, Vicksburg, MS39183 USA • Tel:800-338-2262

www.CAM2.com



## PRODUCT BULLETIN

# SYNAVEX™ Full Synthetic Motor Oil 0W-40

*API SN Plus*

PRODUCT #993

### APPLICATIONS

CAM2 SYNAVEX™ 0W-40 may be recommended for the following uses:

- When SN, SM, SL, SJ, SH, SG, SF, SE, SD or SC oils are required
- ACEA A3/B4-16
- MS-12633 (0W-40), may also be used in SRT engines calling for MS-10725
- MB-229.3, MB-229.5
- Porsche A40
- VW 502.00/503.01/505.00
- Nissan Genuine Performances
- FIAT 9.55535-M2

### TYPICAL PROPERTIES

SAE GRADE	0W-40
Product Code	993
Density, lb/gal	7.18
API Gravity	33.98
Cold Crank Simulation, mPa/s	5800
Viscosity @ 40°C, cSt	88.5
Viscosity @ 100°C, cSt	13.8
Viscosity Index	159
NOACK	<15%
Color ASTM	3
Water And Sediment (Pass/Fail)	Pass
Appearance	Clear
Pour Point: °C	-39
Flash Point: °C	255

Contact your CAM2 representative or CAM2 distributor for additional information.

CAM2 INTERNATIONAL, LLC

685 Haining Road, Vicksburg, MS39183 USA • Tel:800-338-2262

[www.CAM2.com](http://www.CAM2.com)